



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
VOLVO PENTA A394746
 Component
Port Diesel Engine
 Fluid
SHELL ROTELLA T 15W40 (13 LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VPA048691	VPA048693	VPA048695
Sample Date		Client Info		11 Apr 2024	22 Jun 2023	06 Mar 2023
Machine Age	hrs	Client Info		776	693	469
Oil Age	hrs	Client Info		83	224	182
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>80	6	18	10
Chromium	ppm	ASTM D5185m	>6	<1	3	2
Nickel	ppm	ASTM D5185m	>2	<1	4	1
Titanium	ppm	ASTM D5185m	>2	<1	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	2	5	7
Lead	ppm	ASTM D5185m	>95	<1	2	<1
Copper	ppm	ASTM D5185m	>85	2	5	3
Tin	ppm	ASTM D5185m	>9	0	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	5	9	8
Potassium	ppm	ASTM D5185m	>20	3	3	3
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844		0.1	0.2	0.2
Nitration	Abs/cm	*ASTM D7624	>20	6.0	6.6	6.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.0	20.0	19.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		1	4	4
Boron	ppm	ASTM D5185m	316	144	7	17
Barium	ppm	ASTM D5185m	0.0	0	<1	<1
Molybdenum	ppm	ASTM D5185m	1.2	14	59	38
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	24	308	954	614
Calcium	ppm	ASTM D5185m	2292	2306	1149	840
Phosphorus	ppm	ASTM D5185m	1064	1216	1008	664
Zinc	ppm	ASTM D5185m	1160	1525	1258	832
Sulfur	ppm	ASTM D5185m	4996	4914	3722	2479
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.9	15.2	15.4
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	8.6	10.0	10.1
Visc @ 100°C	cSt	ASTM D445	15.7	14.1	13.1	13.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VPA048691 **Received** : 28 Jun 2024
Lab Number : 06223284 **Tested** : 01 Jul 2024
Unique Number : 11101481 **Diagnosed** : 01 Jul 2024 - Don Baldridge
Test Package : MOB 1 (Additional Tests: TBN)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

MARK RAY
 411 WALNUT ST 19430
 GREEN COVE SPRING, FL
 US 32043
 Contact: MARK RAY
 BJMR1122@GMAIL.COM
 T: (303)947-4641
 F: