



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION

Machine Id
HAMM H12I H2840084
 Component
Diesel Engine
 Fluid
JOHN DEERE ENGINE OIL PLUS 50 II 15W40 (--- QTS)

RECOMMENDATION

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0225397	JR0187736	JR0160207
Sample Date		Client Info		27 Jun 2024	11 Sep 2023	22 Feb 2023
Machine Age	hrs	Client Info		1509	946	455
Oil Age	hrs	Client Info		1509	491	0
Filter Age	hrs	Client Info		1509	491	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				ATTENTION	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	34	35	34
Chromium	ppm	ASTM D5185m	>20	1	1	1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	4	<1	4
Lead	ppm	ASTM D5185m	>40	<1	3	2
Copper	ppm	ASTM D5185m	>330	3	6	15
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION










Fuel content negligible. There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	15	20	28
Potassium	ppm	ASTM D5185m	>20	2	3	4
Fuel	%	ASTM D3524	>5	0.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.5	0.4	0.2
Nitration	Abs/cm	*ASTM D7624	>20	7.9	9.2	10.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.2	22.6	19.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The oil viscosity is lower than normal. The BN result indicates that there is suitable alkalinity remaining in the oil. Confirm oil type.

Sodium	ppm	ASTM D5185m		2	3	4
Boron	ppm	ASTM D5185m		126	137	48
Barium	ppm	ASTM D5185m		<1	0	3
Molybdenum	ppm	ASTM D5185m		140	233	82
Manganese	ppm	ASTM D5185m		<1	1	2
Magnesium	ppm	ASTM D5185m		529	761	96
Calcium	ppm	ASTM D5185m		2490	1774	2220
Phosphorus	ppm	ASTM D5185m		1115	884	973
Zinc	ppm	ASTM D5185m		1414	1157	1203
Sulfur	ppm	ASTM D5185m		4267	3856	4421
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.9	17.1	15.2
Base Number (BN)	mg KOH/g	ASTM D2896	13.6	8.4	7.7	6.1
Visc @ 100°C	cSt	ASTM D445	15.4	11.1	12.8	12.5



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0225397 **Received** : 28 Jun 2024
Lab Number : 06223318 **Tested** : 03 Jul 2024
Unique Number : 11101515 **Diagnosed** : 03 Jul 2024 - Jonathan Hester
Test Package : CONST (Additional Tests: FuelDilution, KV40, PercentFuel, TBN)

B & S SITE DEVELOPMENT
 7800 PINEY BRANCH LANE
 BRISTOW, VA
 US 20136
 Contact: DANNY HUFF
 dhuff@bandssite.com
 T: (540)270-3203
 F: (703)753-0605

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)