



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JOHN DEERE 350G 1FF350GXKMF815333
 Component
Right Final Drive
 Fluid
JOHN DEERE GL-5 80W90 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0221942	JR0209647	JR0175254
Sample Date		Client Info		25 Jun 2024	13 Mar 2024	24 Aug 2023
Machine Age	hrs	Client Info		1977	1460	566
Oil Age	hrs	Client Info		1977	1460	566
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		N/A	None	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal. Iron noted.

PQ	UOM	Method	Limit/Abn	Current	History1	History2
PQ		ASTM D8184		107	15	13
Iron	ppm	ASTM D5185m	>500	377	0	1
Chromium	ppm	ASTM D5185m	>10	6	<1	0
Nickel	ppm	ASTM D5185m	>10	2	0	<1
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		<1	0	0
Aluminum	ppm	ASTM D5185m	>25	3	2	<1
Lead	ppm	ASTM D5185m	>25	0	0	<1
Copper	ppm	ASTM D5185m	>50	2	0	<1
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Silicon	ppm	ASTM D5185m	>75	23	<1	2
Potassium	ppm	ASTM D5185m	>20	4	<1	1
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	MODER	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sodium	ppm	ASTM D5185m		3	0	0
Boron	ppm	ASTM D5185m		51	137	123
Barium	ppm	ASTM D5185m		2	0	1
Molybdenum	ppm	ASTM D5185m		0	0	2
Manganese	ppm	ASTM D5185m		8	0	0
Magnesium	ppm	ASTM D5185m		2	1	146
Calcium	ppm	ASTM D5185m		44	4	23
Phosphorus	ppm	ASTM D5185m		494	1136	1683
Zinc	ppm	ASTM D5185m		16	1	13
Sulfur	ppm	ASTM D5185m		18294	21891	27234
Visc @ 40°C	cSt	ASTM D445		183	145	162



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0221942 **Received** : 28 Jun 2024
Lab Number : 06223709 **Tested** : 01 Jul 2024
Unique Number : 11101906 **Diagnosed** : 01 Jul 2024 - Don Baldrige
Test Package : CONST (Additional Tests: PQ)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

JRE - GARNER
 4161 AUBURN CHURCH RD
 GARNER, NC
 US 27529

Contact: RENN MASHBURN
 renn.mashburn@jamesriverequipment.com

T:
 F: (919)779-5432