



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
FORD 343-16
 Component
Diesel Engine
 Fluid
DURALENE Dura-Max 15W40 (14 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		DC0036514	DC0036629	DC0027684
Sample Date		Client Info		20 Jun 2024	04 Jun 2024	04 Apr 2024
Machine Age	mls	Client Info		297624	291903	286143
Oil Age	mls	Client Info		5000	5760	5000
Filter Age	mls	Client Info		5000	5760	5000
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	7	45	4
Chromium	ppm	ASTM D5185m	>20	<1	8	0
Nickel	ppm	ASTM D5185m	>2	<1	<1	0
Titanium	ppm	ASTM D5185m	>2	<1	<1	0
Silver	ppm	ASTM D5185m	>2	<1	6	0
Aluminum	ppm	ASTM D5185m	>25	2	5	<1
Lead	ppm	ASTM D5185m	>40	0	41	0
Copper	ppm	ASTM D5185m	>330	1	9	0
Tin	ppm	ASTM D5185m	>15	0	3	0
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	4	42	3
Potassium	ppm	ASTM D5185m	>20	2	22	0
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.3	0.1
Nitration	Abs/cm	*ASTM D7624	>20	6.9	7.9	7.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	16.7	20.2	16.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		1	47	0
Boron	ppm	ASTM D5185m		4	1	1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		4	7	1
Manganese	ppm	ASTM D5185m		0	2	<1
Magnesium	ppm	ASTM D5185m		52	45	41
Calcium	ppm	ASTM D5185m		2249	2311	2285
Phosphorus	ppm	ASTM D5185m		912	893	862
Zinc	ppm	ASTM D5185m		1054	1095	1012
Sulfur	ppm	ASTM D5185m		3449	3982	3955
Oxidation	Abs/.1mm	*ASTM D7414	>25	10.2	12.0	10.1
Base Number (BN)	mg KOH/g	ASTM D2896		6.8	6.6	7.1
Visc @ 100°C	cSt	ASTM D445		13.2	12.9	13.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : DC0036514 **Received** : 28 Jun 2024
Lab Number : 06224163 **Tested** : 01 Jul 2024
Unique Number : 11102360 **Diagnosed** : 01 Jul 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

NEW DIRECTION UTILITIES
 21616 KELSO DR
 HAGERSTOWN, MD
 US 21742
 Contact: GARY BLOYER
 gary@newdirectionutilities.com
 T: (301)714-0083
 F: