



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION

Machine Id
HC2218
Component
Left Track Drive
Fluid
GEAR OIL ISO 220 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0952090	WC0785073	---
Sample Date		Client Info		22 Jun 2024	20 Mar 2023	---
Machine Age	hrs	Client Info		3757	2075	---
Oil Age	hrs	Client Info		1000	1000	---
Filter Age	hrs	Client Info		0	1000	---
Oil Changed		Client Info		N/A	Changed	---
Filter Changed		Client Info		N/A	Changed	---
Sample Status				ATTENTION	NORMAL	---

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>1000	31	186	---
Chromium	ppm	ASTM D5185m	>30	<1	3	---
Nickel	ppm	ASTM D5185m	>7	<1	1	---
Titanium	ppm	ASTM D5185m		<1	<1	---
Silver	ppm	ASTM D5185m		<1	0	---
Aluminum	ppm	ASTM D5185m	>25	3	4	---
Lead	ppm	ASTM D5185m	>50	0	0	---
Copper	ppm	ASTM D5185m	>100	9	14	---
Tin	ppm	ASTM D5185m	>5	<1	1	---
Vanadium	ppm	ASTM D5185m		<1	<1	---
White Metal	scalar	*Visual	NONE	NONE	LIGHT	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---

CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>150	6	8	---
Potassium	ppm	ASTM D5185m	>20	2	3	---
Water		WC Method	>0.2	NEG	NEG	---
Silt	scalar	*Visual	NONE	MODER	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---

FLUID CONDITION

The oil viscosity is lower than normal. Confirm oil type.

Sodium	ppm	ASTM D5185m		0	8	---
Boron	ppm	ASTM D5185m	50	0	6	---
Barium	ppm	ASTM D5185m	15	<1	0	---
Molybdenum	ppm	ASTM D5185m	15	1	<1	---
Manganese	ppm	ASTM D5185m		<1	2	---
Magnesium	ppm	ASTM D5185m	50	7	<1	---
Calcium	ppm	ASTM D5185m	50	18	7	---
Phosphorus	ppm	ASTM D5185m	350	236	62	---
Zinc	ppm	ASTM D5185m	100	170	27	---
Sulfur	ppm	ASTM D5185m	12500	2704	2165	---
Visc @ 40°C	cSt	ASTM D445	220	123	234	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0952090
Lab Number : 06225404
Unique Number : 11103601
Test Package : CONST

Received : 01 Jul 2024
Tested : 02 Jul 2024
Diagnosed : 03 Jul 2024 - Don Baldrige

BUCKNER HEAVY LIFT
 4732 NC 54 EAST
 GRAHAM, NC
 US 27253-9215

Contact: MICHAEL LAWSON
 michael@bucknercompanies.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (336)376-8888
 F: (336)376-4090