



PacLease

# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**8575157**  
 Component  
**Diesel Engine**  
 Fluid  
**MOBIL DELVAC 1300 SUPER 10W30 (--- GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>RPL0014753</b>	RPL0014847	RPL0010147
Sample Date		Client Info		<b>18 Jun 2024</b>	19 Feb 2024	19 Oct 2023
Machine Age	mls	Client Info		<b>70735</b>	50741	27849
Oil Age	mls	Client Info		<b>19991</b>	22892	27849
Filter Age	mls	Client Info		<b>19991</b>	22892	27849
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

## WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	<b>14</b>	19	55
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	1	0
Titanium	ppm	ASTM D5185m		<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m	>3	<b>0</b>	<1	<1
Aluminum	ppm	ASTM D5185m	>20	<b>6</b>	8	24
Lead	ppm	ASTM D5185m	>40	<b>0</b>	2	4
Copper	ppm	ASTM D5185m	>330	<b>&lt;1</b>	5	43
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	2	2
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

## CONTAMINATION









There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>9</b>	12	45
Potassium	ppm	ASTM D5185m	>20	<b>12</b>	27	95
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.3</b>	0.3	0.3
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.7</b>	9.9	11.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>20.9</b>	21.0	22.1
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>1</b>	3	6
Boron	ppm	ASTM D5185m		<b>25</b>	28	20
Barium	ppm	ASTM D5185m		<b>0</b>	0	7
Molybdenum	ppm	ASTM D5185m		<b>48</b>	6	11
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	1	5
Magnesium	ppm	ASTM D5185m		<b>496</b>	704	712
Calcium	ppm	ASTM D5185m		<b>1463</b>	1209	1306
Phosphorus	ppm	ASTM D5185m		<b>711</b>	681	663
Zinc	ppm	ASTM D5185m		<b>854</b>	798	827
Sulfur	ppm	ASTM D5185m		<b>2583</b>	2838	2835
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>19.6</b>	16.4	19.2
Base Number (BN)	mg KOH/g	ASTM D2896	10.5	<b>8.1</b>	5.6	5.1
Visc @ 100°C	cSt	ASTM D445	11.9	<b>10.5</b>	10.8	11.0



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : RPL0014753 **Received** : 01 Jul 2024  
**Lab Number** : 06225484 **Tested** : 03 Jul 2024  
**Unique Number** : 11103681 **Diagnosed** : 03 Jul 2024 - Don Baldridge  
**Test Package** : FLEET ( Additional Tests: KV40 )

**RTL PACLEASE - 7001 - Houston**  
 6300 N. Loop East  
 Houston, TX  
 US 77026  
 Contact: RODNEY BRIGGS  
 briggs@rushenterprises.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: