



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
(00000)
Machine Id
PETERBILT 8464210
Component
Diesel Engine
Fluid
MOBIL DELVAC 1300 SUPER 15W40 (48 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0019258	RPL0015057	RPL0012427
Sample Date		Client Info		24 Apr 2024	09 Oct 2023	03 May 2023
Machine Age	mls	Client Info		167255	142564	0
Oil Age	mls	Client Info		142564	142564	0
Filter Age	mls	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		Not Changd	Not Changd	None
Sample Status				NORMAL	NORMAL	ATTENTION

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>165	21	20	13
Chromium	ppm	ASTM D5185m	>5	1	1	1
Nickel	ppm	ASTM D5185m	>4	0	0	<1
Titanium	ppm	ASTM D5185m	>2	<1	<1	0
Silver	ppm	ASTM D5185m	>2	0	<1	0
Aluminum	ppm	ASTM D5185m	>20	10	7	4
Lead	ppm	ASTM D5185m	>150	<1	2	1
Copper	ppm	ASTM D5185m	>90	1	1	<1
Tin	ppm	ASTM D5185m	>5	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>35	6	5	6
Potassium	ppm	ASTM D5185m	>20	32	22	12
Fuel		WC Method	>3.0	<1.0	2.5	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>7.5	0.2	0.2	0.1
Nitration	Abs/cm	*ASTM D7624	>20	9.8	10.1	8.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.3	24.6	23.8
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	0	2
Boron	ppm	ASTM D5185m	0	37	43	82
Barium	ppm	ASTM D5185m	0	0	0	2
Molybdenum	ppm	ASTM D5185m	0	4	39	41
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	0	680	456	491
Calcium	ppm	ASTM D5185m		1384	1527	1605
Phosphorus	ppm	ASTM D5185m		635	658	748
Zinc	ppm	ASTM D5185m		810	872	913
Sulfur	ppm	ASTM D5185m		3335	2658	2627
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.2	26.1	23.0
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	6.0	6.5	8.6
Visc @ 100°C	cSt	ASTM D445	14	13.0	12.4	12.3



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RPL0019258
Lab Number : 06225857
Unique Number : 11109350
Test Package : FLEET

Received : 02 Jul 2024
Tested : 03 Jul 2024
Diagnosed : 03 Jul 2024 - Wes Davis

RTL PACLEASE - 7006 - Pico Rivera
 7837 Telegraph Rd
 Pico Rivera, CA
 US 90660
 Contact: GERARDO CARROLA
 carrolag@rushenterprises.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: