



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
FORD 8464733
 Component
Diesel Engine
 Fluid
MOTORCRAFT SUPER PREMIUM SAE 10W30 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL0019267	RPL0015869	RPL0011933
Sample Date		Client Info		02 Apr 2024	03 Nov 2023	06 Jul 2023
Machine Age	mls	Client Info		16181	10655	6572
Oil Age	mls	Client Info		10655	10655	6572
Filter Age	mls	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	SEVERE

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	65	20	48
Chromium	ppm	ASTM D5185m	>20	3	<1	3
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m	>2	<1	<1	<1
Silver	ppm	ASTM D5185m	>2	<1	<1	2
Aluminum	ppm	ASTM D5185m	>25	6	3	6
Lead	ppm	ASTM D5185m	>40	0	0	0
Copper	ppm	ASTM D5185m	>330	4	2	10
Tin	ppm	ASTM D5185m	>15	0	0	0
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	9	8	12
Potassium	ppm	ASTM D5185m	>20	2	5	1
Fuel		WC Method	>5	<1.0	1.5	▲ 11.7
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.6	0.2	0.3
Nitration	Abs/cm	*ASTM D7624	>20	10.0	6.5	9.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.4	19.0	20.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		3	<1	3
Boron	ppm	ASTM D5185m		40	95	45
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		11	10	68
Manganese	ppm	ASTM D5185m		2	<1	3
Magnesium	ppm	ASTM D5185m		643	583	117
Calcium	ppm	ASTM D5185m		1442	1327	1916
Phosphorus	ppm	ASTM D5185m		1036	947	945
Zinc	ppm	ASTM D5185m		1218	1132	1113
Sulfur	ppm	ASTM D5185m		4136	3842	4018
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.2	12.6	17.3
Base Number (BN)	mg KOH/g	ASTM D2896	6.7	7.0	8.2	4.8
Visc @ 100°C	cSt	ASTM D445	10.8	10.2	11.1	▲ 8.4


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Non-ferrous Metals




Viscosity @ 100°C



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : RPL0019267

Lab Number : 06225919

Unique Number : 11109412

Test Package : FLEET

Received : 02 Jul 2024

Tested : 03 Jul 2024

Diagnosed : 03 Jul 2024 - Angela Borella

RTL PACLEASE - 7006 - Pico Rivera

7837 Telegraph Rd

Pico Rivera, CA

US 90660

Contact: GERARDO CARROLA

carrolag@rushenterprises.com

T:

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)