



OIL ANALYSIS REPORT

| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Area
[127484]

Machine Id
JOHN DEERE 700L 1DW700LXTNF415486

Component
Left Final Drive

Fluid
JOHN DEERE HY-GARD HYD/TRANS (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|----------|----------|
| Sample Number | | Client Info | | WE0007877 | --- | --- |
| Sample Date | | Client Info | | 28 Jun 2024 | --- | --- |
| Machine Age | hrs | Client Info | | 464 | --- | --- |
| Oil Age | hrs | Client Info | | 0 | --- | --- |
| Filter Age | hrs | Client Info | | 0 | --- | --- |
| Oil Changed | | Client Info | | N/A | --- | --- |
| Filter Changed | | Client Info | | N/A | --- | --- |
| Sample Status | | | | NORMAL | --- | --- |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|-------|--------------|-----|-----|
| PQ | | ASTM D8184 | >1250 | 24 | --- | --- |
| Iron | ppm | ASTM D5185m | >750 | 66 | --- | --- |
| Chromium | ppm | ASTM D5185m | >9 | 1 | --- | --- |
| Nickel | ppm | ASTM D5185m | >10 | <1 | --- | --- |
| Titanium | ppm | ASTM D5185m | | <1 | --- | --- |
| Silver | ppm | ASTM D5185m | | <1 | --- | --- |
| Aluminum | ppm | ASTM D5185m | >40 | 3 | --- | --- |
| Lead | ppm | ASTM D5185m | >15 | <1 | --- | --- |
| Copper | ppm | ASTM D5185m | >40 | <1 | --- | --- |
| Tin | ppm | ASTM D5185m | >10 | <1 | --- | --- |
| Vanadium | ppm | ASTM D5185m | | <1 | --- | --- |
| White Metal | scalar | *Visual | NONE | NONE | --- | --- |
| Yellow Metal | scalar | *Visual | NONE | NONE | --- | --- |

CONTAMINATION






There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|--------|-------------|--------|--------------|-----|-----|
| Silicon | ppm | ASTM D5185m | >75 | 11 | --- | --- |
| Potassium | ppm | ASTM D5185m | >20 | 13 | --- | --- |
| Water | | WC Method | >0.075 | NEG | --- | --- |
| Silt | scalar | *Visual | NONE | NONE | --- | --- |
| Debris | scalar | *Visual | NONE | NONE | --- | --- |
| Sand/Dirt | scalar | *Visual | NONE | NONE | --- | --- |
| Appearance | scalar | *Visual | NORML | NORML | --- | --- |
| Odor | scalar | *Visual | NORML | NORML | --- | --- |
| Emulsified Water | scalar | *Visual | >0.075 | NEG | --- | --- |

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

| | | | | | | |
|-------------|-----|-------------|------|--------------|-----|-----|
| Sodium | ppm | ASTM D5185m | >51 | 3 | --- | --- |
| Boron | ppm | ASTM D5185m | 6 | 4 | --- | --- |
| Barium | ppm | ASTM D5185m | 0 | <1 | --- | --- |
| Molybdenum | ppm | ASTM D5185m | 0 | 3 | --- | --- |
| Manganese | ppm | ASTM D5185m | | 2 | --- | --- |
| Magnesium | ppm | ASTM D5185m | 145 | 105 | --- | --- |
| Calcium | ppm | ASTM D5185m | 3570 | 3566 | --- | --- |
| Phosphorus | ppm | ASTM D5185m | 1290 | 1116 | --- | --- |
| Zinc | ppm | ASTM D5185m | 1640 | 1300 | --- | --- |
| Sulfur | ppm | ASTM D5185m | | 3783 | --- | --- |
| Visc @ 40°C | cSt | ASTM D445 | 57.0 | 51.8 | --- | --- |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : WE0007877

Lab Number : 06226489

Unique Number : 11109982

Test Package : CONST (Additional Tests: PQ)

Received : 02 Jul 2024

Tested : 03 Jul 2024

Diagnosed : 03 Jul 2024 - Wes Davis

WARRIOR TRACTOR AND EQUIPMENT - NORTHPORT

P.O. BOX 412

NORTHPORT, AL

US 35476

Contact: CRAIG ANDOE

serve01@warriortractor.com

T: (205)339-0300

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)