
WEAR CONTAMINATION FLUID CONDITION


NORMAL NORMAL


Machine Id
HC2236
Component
Gearbox


GEAR OIL ISO 220 (--- GAL)

GEAR OIL ISO 220 (GAL)							
RECOMMENDATION	Test	UOM	Method	Limit/Abn	Current	History1	History2
Resample at the next service interval to monitor.	Sample Number		Client Info		WC0952130	WC0867440	
resumple at the next service interval to monitor.	Sample Date		Client Info		26 Jun 2024	02 Dec 2023	
	Machine Age	hrs	Client Info		3339	2803	
	Oil Age	hrs	Client Info		536	0	
	Filter Age	hrs	Client Info		0	0	
	Oil Changed		Client Info		Changed	Changed	
	Filter Changed		Client Info		Not Changd	Changed	
	Sample Status				NORMAL	ATTENTION	
WEAD							
WEAR	Iron	ppm	ASTM D5185m		106	29	
All component wear rates are normal.	Chromium	ppm	ASTM D5185m		<1	0	
	Nickel	ppm	ASTM D5185m	>10	0	0	
	Titanium	ppm	ASTM D5185m		0	0	
	Silver	ppm	ASTM D5185m		0	0	
	Aluminum	ppm	ASTM D5185m		21	5	
	Lead	ppm	ASTM D5185m		0	0	
	Copper	ppm	ASTM D5185m	>200	<1	0	
	Tin	ppm	ASTM D5185m	>10	0	<1	
	Vanadium	ppm	ASTM D5185m		0	0	
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
CONTAMINATION	Silicon	ppm	ASTM D5185m	>50	3	3	
There is no indication of any contamination in the oil.	Potassium	ppm	ASTM D5185m	>20	2	1	
There is no indication of any contamination in the oil.	Water		WC Method	>0.2	NEG	NEG	
	Silt	scalar	*Visual	NONE	NONE	MODER	
	Debris	scalar	*Visual	NONE	NONE	NONE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
	Appearance	scalar	*Visual	NORML	NORML	NORML	
	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	
FLUID CONDITION	Sodium	ppm	ASTM D5185m		0	0	
The condition of the oil is acceptable for the time in service.	Boron	ppm	ASTM D5185m	50	4	<1	
The condition of the on is acceptable for the time in service.	Barium	ppm	ASTM D5185m	15	0	0	
	Molybdenum	ppm	ASTM D5185m	15	0	0	
	Manganese	ppm	ASTM D5185m		<1	<1	
	Magnesium	ppm	ASTM D5185m	50	0	<1	
	Calcium	ppm	ASTM D5185m	50	0	0	
	Phosphorus	ppm	ASTM D5185m	350	408	284	
	Zinc	ppm	ASTM D5185m	100	43	36	
	Sulfur	ppm	ASTM D5185m	12500	4722	4636	
	Visc @ 40°C	cSt	ASTM D445		226	177	
Papart Id: PLICCEA [WILECAP] 06226574 (Caparated: 07/00/2024 17:26:20) Pay: 1					ion: MICHAE		DUCCDA











Certificate L2367

Laboratory Sample No.

: WC0952130 Lab Number : 06226574 Unique Number : 11110067 Test Package : CONST

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 02 Jul 2024 **Tested** : 03 Jul 2024

Diagnosed : 05 Jul 2024 - Don Baldridge **BUCKNER HEAVY LIFT**

4732 NC 54 EAST GRAHAM, NC US 27253-9215

Contact: MICHAEL LAWSON michaell@bucknercompanies.com

T: (336)376-8888 F: (336)376-4090

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)