



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
Store 2 - Beaver [RO#152250]
Machine Id
JOHN DEERE 130GL 1FF130GXKEE040620
Component
Swing Drive
Fluid
JOHN DEERE HY-GARD HYD/TRANS (1 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0051126	LEC0011200	LECP190712
Sample Date		Client Info		21 Jun 2024	02 Apr 2020	18 Jan 2019
Machine Age	hrs	Client Info		3210	2804	2195
Oil Age	hrs	Client Info		406	609	1136
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Chngd	Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ	UOM	Method	Limit/Abn	Current	History1	History2
PQ		ASTM D8184		30	35	32
Iron	ppm	ASTM D5185m	>151	170	126	90
Chromium	ppm	ASTM D5185m	>11	1	2	1
Nickel	ppm	ASTM D5185m	>10	0	<1	0
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		1	0	0
Aluminum	ppm	ASTM D5185m	>21	<1	1	2
Lead	ppm	ASTM D5185m	>51	0	0	0
Copper	ppm	ASTM D5185m	>51	0	<1	<1
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>31	16	21	20
Potassium	ppm	ASTM D5185m	>20	12	4	2
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	2	1	<1
Boron	ppm	ASTM D5185m	6	34	29	56
Barium	ppm	ASTM D5185m	0	5	4	14
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		2	2	3
Magnesium	ppm	ASTM D5185m	145	71	80	<1
Calcium	ppm	ASTM D5185m	3570	2507	2819	16
Phosphorus	ppm	ASTM D5185m	1290	888	850	538
Zinc	ppm	ASTM D5185m	1640	922	925	24
Sulfur	ppm	ASTM D5185m		7231	5343	19926
Visc @ 40°C	cSt	ASTM D445	57.0	67.1	69.1	178.1



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0051126 **Received** : 03 Jul 2024
Lab Number : 06227826 **Tested** : 05 Jul 2024
Unique Number : 11111319 **Diagnosed** : 07 Jul 2024 - Don Baldrige
Test Package : CONST (Additional Tests: PQ)

LESLIE EQUIPMENT COMPANY
 105 TENNIS CENTER DR.
 MARIETTA, OH
 US 45750-9765
 Contact: LEANNE KENDALL
 KendalLeanne@lec1.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (740)373-5570