



# OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**DE Samples - CAT LAB**  
Machine Id  
**CATERPILLAR 420 FST BACKHOE 6010 (S/N SKR04232)**  
Component  
**Transmission (Manual)**  
Fluid  
**TULCO LUBSOIL TO-4 30 (--- GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>TO10003638</b>	TO10002038	TO10002851
Sample Date		Client Info		<b>01 Jul 2024</b>	15 Mar 2024	14 Nov 2023
Machine Age	hrs	Client Info		<b>13787</b>	13344	12883
Oil Age	hrs	Client Info		<b>904</b>	461	896
Filter Age	hrs	Client Info		<b>904</b>	461	573
Oil Changed		Client Info		<b>Changed</b>	Not Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

## WEAR

All component wear rates are normal.

PQ		ASTM D8184	>95	<b>23</b>	14	15
Iron	ppm	ASTM D5185m	>200	<b>9</b>	5	6
Chromium	ppm	ASTM D5185m	>5	<b>0</b>	0	0
Nickel	ppm	ASTM D5185m	>5	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>7	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>2</b>	1	2
Lead	ppm	ASTM D5185m	>45	<b>1</b>	<1	0
Copper	ppm	ASTM D5185m	>225	<b>5</b>	3	3
Tin	ppm	ASTM D5185m	>10	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

## CONTAMINATION













There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>125	<b>15</b>	11	14
Potassium	ppm	ASTM D5185m	>20	<b>3</b>	<1	0
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>LIGHT</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>4</b>	5	2
Boron	ppm	ASTM D5185m		<b>0</b>	0	0
Barium	ppm	ASTM D5185m		<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m		<b>0</b>	0	0
Manganese	ppm	ASTM D5185m		<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m	9	<b>15</b>	15	13
Calcium	ppm	ASTM D5185m	4500	<b>3570</b>	3219	3064
Phosphorus	ppm	ASTM D5185m	1150	<b>1005</b>	917	886
Zinc	ppm	ASTM D5185m	1250	<b>1214</b>	1124	1089
Sulfur	ppm	ASTM D5185m	4500	<b>5330</b>	4940	4117
Acid Number (AN)	mg KOH/g	ASTM D8045	0.28	<b>1.01</b>	1.02	0.88
Visc @ 40°C	cSt	ASTM D445	108	<b>105</b>	107	105
Visc @ 100°C	cSt	ASTM D445	11.6	<b>11.5</b>	11.8	11.7
Viscosity Index (VI)	Scale	ASTM D2270	94	<b>95</b>	98	98



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : TO10003638 **Received** : 05 Jul 2024  
**Lab Number** : 06229247 **Tested** : 09 Jul 2024  
**Unique Number** : 11112740 **Diagnosed** : 09 Jul 2024 - Wes Davis  
**Test Package** : MOB 2 ( Additional Tests: KV100, PQ, VI )

**ANCHOR STONE TULSA ROCK**  
 TULSA ROCK QUARRY, 66TH ST N 145TH AVENUE  
 TULSA, OK  
 US 74137  
 Contact: MIKE SNYDER  
 msnyder@anchorstoneco.com  
 T: (417)850-9635  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)