



WEAR CHECK

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
59067
 Component
Diesel Engine
 Fluid
SHELL ROTELLA T 15W40 (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0866961	WC0866982	WC0820929
Sample Date		Client Info		29 May 2024	12 Dec 2023	17 Jun 2023
Machine Age	mls	Client Info		306231	284151	265576
Oil Age	mls	Client Info		22080	16306	0
Filter Age	mls	Client Info		22080	16306	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	90	20	<1
Chromium	ppm	ASTM D5185m	>20	3	<1	0
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	39	5	2
Lead	ppm	ASTM D5185m	>40	23	16	0
Copper	ppm	ASTM D5185m	>330	1	2	0
Tin	ppm	ASTM D5185m	>15	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION









There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	16	5	3
Potassium	ppm	ASTM D5185m	>20	85	11	1
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	1.1	0.6	0.1
Nitration	Abs/cm	*ASTM D7624	>20	14.2	12.4	6.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	35.3	25.6	19.1
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		4	2	<1
Boron	ppm	ASTM D5185m	316	73	9	0
Barium	ppm	ASTM D5185m	0.0	<1	0	4
Molybdenum	ppm	ASTM D5185m	1.2	97	69	54
Manganese	ppm	ASTM D5185m		1	<1	0
Magnesium	ppm	ASTM D5185m	24	662	1050	850
Calcium	ppm	ASTM D5185m	2292	1685	1191	960
Phosphorus	ppm	ASTM D5185m	1064	1207	1145	911
Zinc	ppm	ASTM D5185m	1160	1501	1404	1128
Sulfur	ppm	ASTM D5185m	4996	3842	3231	3523
Oxidation	Abs/.1mm	*ASTM D7414	>25	34.2	24.2	15.6
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	4.4	7.6	9.5
Visc @ 100°C	cSt	ASTM D445	15.7	15.2	14.4	13.3



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0866961
Lab Number : 06229565
Unique Number : 11113058
Test Package : FLEET

Received : 05 Jul 2024
Tested : 09 Jul 2024
Diagnosed : 09 Jul 2024 - Jonathan Hester

SALEM NATIONALEASE CORPORATION
 198 PARK PLAZA DRIVE
 WINSTON SALEM, NC
 US 27105

Contact: Audrey Hopkins
 Audrey.Hopkins@salemcorp.com
 T: (336)767-9642

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: x: