



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**413065**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0123581</b>	GFL0112034	GFL0105480
Sample Date		Client Info		<b>01 Jul 2024</b>	12 Apr 2024	31 Jan 2024
Machine Age	mls	Client Info		<b>58077</b>	49996	41276
Oil Age	mls	Client Info		<b>58077</b>	49996	41276
Filter Age	mls	Client Info		<b>0</b>	49996	0
Oil Changed		Client Info		<b>Not Chngd</b>	Changed	N/A
Filter Changed		Client Info		<b>Not Chngd</b>	Changed	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>5</b>	7	4
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	1	0
Nickel	ppm	ASTM D5185m	>5	<b>&lt;1</b>	2	0
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	0
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	1	<1
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	1	0
Copper	ppm	ASTM D5185m	>330	<b>3</b>	3	3
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	1	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	<b>6</b>	7	7
Potassium	ppm	ASTM D5185m	>20	<b>6</b>	6	2
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>0.2</b>	0.2	0.1
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.8</b>	8.3	7.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>18.7</b>	20.2	19.9
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>4</b>	2	2
Boron	ppm	ASTM D5185m	0	<b>&lt;1</b>	0	0
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>51</b>	54	55
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	1	0
Magnesium	ppm	ASTM D5185m	1010	<b>6</b>	6	4
Calcium	ppm	ASTM D5185m	1070	<b>2484</b>	2565	2487
Phosphorus	ppm	ASTM D5185m	1150	<b>1034</b>	1219	1120
Zinc	ppm	ASTM D5185m	1270	<b>1261</b>	1276	1299
Sulfur	ppm	ASTM D5185m	2060	<b>2977</b>	3753	3345
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>10.9</b>	12.0	11.6
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>6.1</b>	6.2	6.0
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.2</b>	12.6	13.0


**FT-IR (Direct Trend)**




**Base Number**




**Viscosity @ 100°C**




**Ferrous Alloys**




**Non-ferrous Metals**



**Viscosity @ 100°C**



**Base Number**



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0123581  
**Lab Number** : 06229878  
**Unique Number** : 11113371  
**Test Package** : FLEET

**Received** : 08 Jul 2024  
**Tested** : 09 Jul 2024  
**Diagnosed** : 09 Jul 2024 - Don Baldrige

**GFL Environmental - 983 - Sugar Land Hauling**  
 16011 West Belfort Street  
 Sugar Land, TX  
 US 77498  
 Contact: Adrian Martinez  
 adrianmartinez@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: