## CORROSION CONTAMINANTS COOLANT CONDITION

NORMAL NORMAL NORMAL

WCLSNC Machine Id

## QC COOL ELC NC 09012022

Coolant Coolant

CAT EXTENDED LIFE COOLANT (ELC) (--- GAL)

| CAT EXTENDED LIFE COOLANT (ELC) ( GAL  | <del>-</del> /         |            |             |           |             |              |           |
|--|------------------------|------------|-------------|-----------|-------------|--------------|-----------|
| RECOMMENDATION   | Test                   | UOM        | Method      | Limit/Abn | Current     | History1     | History2  |
| No corrective action is recommended at this time. The fluid is suitable for further service.                                   | Sample Number          |            | Client Info |           | WC0961109   | WC0961106    | WC09611   |
|  | Sample Date            |            | Client Info |           | 08 Jul 2024 | 05 Jul 2024  | 03 Jul 20 |
|  | Machine Age            | hrs        | Client Info |           | 0           | 0            | 0         |
|  | Oil Age                | hrs        | Client Info |           | 0           | 0            | 0         |
|  | Oil Changed            |            | Client Info |           | N/A         | N/A          | N/A       |
|  | Sample Status          |            |             |           | NORMAL      | SEVERE       | NORMA     |
| CORROSION  | Iron                   | ppm        | ASTM D6130  | >2        | 0           | 0            | 0         |
| All metal levels are normal indicating no corrosion in the cooling system.   | Aluminum               | ppm        | ASTM D6130  | >2        | 0           | 0            | <1        |
|  | Copper                 | ppm        | ASTM D6130  | >2        | 0           | 0            | 0         |
|  | Lead                   | ppm        | ASTM D6130  | >2        | 0           | 0            | <1        |
|  | Tin                    | ppm        | ASTM D6130  | >2        | 0           | 0            | 0         |
|  | Zinc                   | ppm        | ASTM D6130  | >10       | 0           | 0            | 0         |
| CONTAMINANTS   | Calcium                | ppm        | ASTM D6130  | >5        | 0           | 0            | 0         |
| There is no indication of any contamination in the coolant.  | Chlorine               | ppm        | ASTM D6130  |           | 1           | 0            | 2         |
|  | Magnesium              | ppm        | ASTM D6130  | >6        | 0           | 0            | 0         |
|  | Total Dissolved Solids |            |             |           | 318.0       | 295.5        | 245.0     |
|  | Coolant Appearance     |            | *Visual     | Clear     | normal      | normal       | norm      |
| COOLANT CONDITION  | Boiling Point          | °C         | WC Method   |           | 225         | 225          | 225       |
| Carboxylate test failed. Glycol and nitrite levels are acceptable. The pH level of this fluid is within the acceptable limits. | Specific Gravity       |            | *ASTM D1298 |           | 1.066       | 1.066        | 1.065     |
|  | рН                     | Scale 0-14 | ASTM D1287  |           | 8.12        | 8.13         | 8.16      |
|  | Nitrites               | ppm        | AP-053:2009 |           | 788         | 824          | 712       |
|  | Reserve Alkalinity     | Scale 0-20 | *ASTM D1121 |           |             |              |           |
|  | Percentage Glycol      | %          | ASTM D3321  |           | 49.0        | 49.0         | 48.4      |
|  | Freezing Point         | °F         | ASTM D3321  |           | -33         | -33          | -31       |
|  | Carboxylate            |            |             |           | fail        | ▲ fail       | fail      |
|  | Silicon                | ppm        | ASTM D6130  |           | <1          | 1            | 1         |
|  | Phosphorus             | ppm        | ASTM D6130  | 0         | 0           | 0            | 0         |
|  | Boron                  | ppm        | ASTM D6130  | 0         | 0           | 0            | 0         |
|  | Molybdenum             | ppm        | ASTM D6130  | 950       | 798         | <b>△</b> 640 | 755       |
|  | Sodium                 | ppm        | ASTM D6130  |           | 4756        | 3716         | 3904      |
|  | Potassium              | ppm        | ASTM D6130  |           | 3           | 9            | 8         |
|  | Coolant Color          |            | *Visual     |           | Red         | Red          | Red       |





Certificate L2367

Laboratory Sample No.

Lab Number : 06230702

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : WC0961109

**Tested** Unique Number : 11114195 Diagnosed Test Package: COOL- (Additional Tests: GlycolType, ICP)

: 11 Jul 2024 - Jonathan Hester

: 08 Jul 2024

: 11 Jul 2024

Received

501 Madison Ave Cary, NC US 27513

Contact: WCLS CARY NC

WEARCHECK LUBRICATION SERVICES QA ACCOUNT

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (919)379-4102 F: (919)379-4050