



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
525100
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (40 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0110764	GFL0110783	GFL0092868
Sample Date		Client Info		02 Jul 2024	28 Mar 2024	11 Dec 2023
Machine Age	mls	Client Info		656341	634301	615712
Oil Age	mls	Client Info		22040	18589	47386
Filter Age	mls	Client Info		22040	18589	47386
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>110	35	27	28
Chromium	ppm	ASTM D5185m	>4	<1	<1	1
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	9	8	8
Lead	ppm	ASTM D5185m	>45	3	1	2
Copper	ppm	ASTM D5185m	>85	<1	1	1
Tin	ppm	ASTM D5185m	>4	0	0	<1
Vanadium	ppm	ASTM D5185m		0	<1	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>30	4	3	4
Potassium	ppm	ASTM D5185m	>20	3	2	6
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	1	1	1.1
Nitration	Abs/cm	*ASTM D7624	>20	12.5	11.4	12.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.1	22.8	24.1
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		5	2	<1
Boron	ppm	ASTM D5185m	0	5	3	7
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	67	60	64
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	1010	1144	986	984
Calcium	ppm	ASTM D5185m	1070	1361	1185	1103
Phosphorus	ppm	ASTM D5185m	1150	1221	1077	972
Zinc	ppm	ASTM D5185m	1270	1481	1294	1268
Sulfur	ppm	ASTM D5185m	2060	3820	3468	3058
Oxidation	Abs/.1mm	*ASTM D7414	>25	21.5	19.4	20.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	6.4	7.6	7.1
Visc @ 100°C	cSt	ASTM D445	15.4	14.6	14.2	14.3


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Non-ferrous Metals




Viscosity @ 100°C



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : GFL0110764
 Lab Number : 06231130
 Unique Number : 11114623
 Test Package : FLEET

Received : 08 Jul 2024
 Tested : 10 Jul 2024
 Diagnosed : 10 Jul 2024 - Wes Davis

GFL Environmental - 411 - Kingsford HC
 1001 E Blvd
 Kingsford, MI
 US 49802
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: