



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[W67997]
 Machine Id
JOHN DEERE 410E 1DW410ETKJF692851
 Component
Transmission (Auto)
 Fluid
JOHN DEERE HD SynTran (13 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. (Customer Sample Comment: W67997)

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0216090	JR0085985	JR0079822
Sample Date		Client Info		08 Jul 2024	20 May 2021	01 Mar 2021
Machine Age	hrs	Client Info		5511	5004	4568
Oil Age	hrs	Client Info		4773	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Not Changd	Not Changd
Filter Changed		Client Info		N/A	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>50	19	39	35
Iron	ppm	ASTM D5185m	>160	46	94	85
Chromium	ppm	ASTM D5185m	>5	0	<1	<1
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>50	<1	2	<1
Lead	ppm	ASTM D5185m	>50	0	0	<1
Copper	ppm	ASTM D5185m	>225	1	1	1
Tin	ppm	ASTM D5185m	>10	0	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>20	1	1	2
Potassium	ppm	ASTM D5185m	>20	<1	<1	<1
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	LIGHT	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	VLITE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		3	2	0
Boron	ppm	ASTM D5185m	168	95	126	136
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	<1	<1
Manganese	ppm	ASTM D5185m		<1	1	<1
Magnesium	ppm	ASTM D5185m		2	<1	2
Calcium	ppm	ASTM D5185m	33	60	66	61
Phosphorus	ppm	ASTM D5185m	330	268	283	282
Zinc	ppm	ASTM D5185m	0	12	7	5
Sulfur	ppm	ASTM D5185m	980	321	453	461
Visc @ 40°C	cSt	ASTM D445	39	37.6	36.8	36.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0216090 **Received** : 10 Jul 2024
Lab Number : 06232421 **Tested** : 11 Jul 2024
Unique Number : 11115914 **Diagnosed** : 11 Jul 2024 - Sean Felton
Test Package : CONST (Additional Tests: PQ)

JRE - CHARLOTTE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269
 Contact: CHARLOTTE SHOP
 myoung@jamesriverequipment.com
 T: (704)597-0211
 F: (704)596-6198

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)