



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
[W67259]

Machine Id
JOHN DEERE 300G 1FF300GXJNF731921

Component
Right Final Drive

Fluid
JOHN DEERE GL-5 80W90 (2 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. (Customer Sample Comment: W67259)

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0216103	JR0188817	JR0171039
Sample Date		Client Info		08 Jul 2024	05 Nov 2023	17 Jul 2023
Machine Age	hrs	Client Info		2200	1517	1046
Oil Age	hrs	Client Info		2200	1517	1046
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Filter Changed		Client Info		N/A	Not Changd	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	90	14	22
Iron	ppm	ASTM D5185m	>750	172	1	43
Chromium	ppm	ASTM D5185m	>9	3	<1	<1
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>40	1	1	0
Lead	ppm	ASTM D5185m	>15	0	0	0
Copper	ppm	ASTM D5185m	>40	<1	<1	0
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the component.

Silicon	ppm	ASTM D5185m	>75	7	1	15
Potassium	ppm	ASTM D5185m	>20	4	<1	0
Water		WC Method	>0.075	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	3	0	3
Boron	ppm	ASTM D5185m		48	2	111
Barium	ppm	ASTM D5185m		4	0	0
Molybdenum	ppm	ASTM D5185m		0	<1	0
Manganese	ppm	ASTM D5185m		3	0	2
Magnesium	ppm	ASTM D5185m		2	5	<1
Calcium	ppm	ASTM D5185m		17	11	62
Phosphorus	ppm	ASTM D5185m		489	899	526
Zinc	ppm	ASTM D5185m		31	0	14
Sulfur	ppm	ASTM D5185m		16004	23351	18171
Visc @ 40°C	cSt	ASTM D445		184	179	185



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0216103 **Received** : 10 Jul 2024
Lab Number : 06232439 **Tested** : 11 Jul 2024
Unique Number : 11115932 **Diagnosed** : 11 Jul 2024 - Sean Felton
Test Package : CONST (Additional Tests: PQ)

JRE - CHARLOTTE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269
 Contact: CHARLOTTE SHOP
 myoung@jamesriverequipment.com
 T: (704)597-0211
 F: (704)596-6198

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)