



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
AW 68
 Component
New (Unused) Oil
 Fluid
ISO 68 (--- LTR)

RECOMMENDATION

This is a baseline read-out on the submitted sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		DC0033740	DC0033919	DC0035523
Sample Date		Client Info		14 Jun 2024	17 May 2024	15 Apr 2024
Machine Age	mls	Client Info		0	0	0
Oil Age	mls	Client Info		0	0	0
Filter Age	mls	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR















Iron	ppm	ASTM D5185m		0	0	0
Chromium	ppm	ASTM D5185m		<1	0	0
Nickel	ppm	ASTM D5185m		0	<1	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m		3	0	0
Lead	ppm	ASTM D5185m		<1	0	0
Copper	ppm	ASTM D5185m		<1	0	0
Tin	ppm	ASTM D5185m		<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

Silicon	ppm	ASTM D5185m		0	<1	0
Potassium	ppm	ASTM D5185m	>20	1	2	0
Water		WC Method		NEG	NEG	NEG
Particles >4µm		ASTM D7647	>5000	438	343	337
Particles >6µm		ASTM D7647	>1300	86	102	94
Particles >14µm		ASTM D7647	>160	8	11	8
Particles >21µm		ASTM D7647	>40	3	3	3
Particles >38µm		ASTM D7647	>10	1	1	0
Particles >71µm		ASTM D7647	>3	1	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	16/14/10	16/14/11	16/14/10
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual		NEG	NEG	NEG

FLUID CONDITION

Sodium	ppm	ASTM D5185m		0	3	1
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m		63	102	87
Calcium	ppm	ASTM D5185m		60	76	70
Phosphorus	ppm	ASTM D5185m		196	321	340
Zinc	ppm	ASTM D5185m		258	404	382
Sulfur	ppm	ASTM D5185m		6781	8005	7855
Acid Number (AN)	mg KOH/g	ASTM D8045		0.29	0.40	0.42
Visc @ 40°C	cSt	ASTM D445	68.0	65.48	64.22	64.16
Visc @ 100°C	cSt	ASTM D445	9.5	8.78	8.7	8.89
Viscosity Index (VI)	Scale	ASTM D2270	118	106	107	113



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : DC0033740
Lab Number : 06232677
Unique Number : 11116170
Test Package : MOB 2 (Additional Tests: FT-IR, ICP-NewOil, KV100, PrtCount, VI)

THE UNITED OIL COMPANY - OPERATIONS
 4405 E. BALTIMORE ST
 BALTIMORE, MD
 US 21224
 Contact: MICHELLE HORNING

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: (410)327-7695