



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
Enviromental
 Machine Id
RTO 5 Hydraulic Unit (S/N EN252)
 Component
Hydraulic System
 Fluid
DEXRON III (30 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DEXRON III. Please confirm.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0895156	WC0895143	WC0895066
Sample Date		Client Info		08 Jul 2024	30 May 2024	23 Apr 2024
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>20	14	15	17
Chromium	ppm	ASTM D5185m	>20	0	0	<1
Nickel	ppm	ASTM D5185m	>20	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	0	<1	2
Lead	ppm	ASTM D5185m	>20	0	<1	2
Copper	ppm	ASTM D5185m	>20	18	21	21
Tin	ppm	ASTM D5185m	>20	0	1	1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Silicon	ppm	ASTM D5185m	>15	<1	2	2
Potassium	ppm	ASTM D5185m	>20	0	2	2
Water		WC Method	>0.05	NEG	NEG	NEG
Particles >4µm		ASTM D7647	>2500	144	601	1570
Particles >6µm		ASTM D7647	>640	31	46	49
Particles >14µm		ASTM D7647	>80	3	6	3
Particles >21µm		ASTM D7647	>20	1	2	1
Particles >38µm		ASTM D7647	>4	0	0	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>18/16/13	14/12/9	16/13/10	18/13/9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		11	12	10
Boron	ppm	ASTM D5185m		71	88	84
Barium	ppm	ASTM D5185m		0	0	<1
Molybdenum	ppm	ASTM D5185m		0	0	<1
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		2	1	2
Calcium	ppm	ASTM D5185m		85	85	89
Phosphorus	ppm	ASTM D5185m		248	242	246
Zinc	ppm	ASTM D5185m		35	28	28
Sulfur	ppm	ASTM D5185m		1041	959	893
Acid Number (AN)	mg KOH/g	ASTM D8045		0.70	0.76	0.74
Visc @ 40°C	cSt	ASTM D445	35.0	26.5	25.8	25.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : WC0895156

Lab Number : 06233828

Unique Number : 11122662

Test Package : IND 2

Received : 11 Jul 2024

Tested : 12 Jul 2024

Diagnosed : 12 Jul 2024 - Wes Davis

J.M. Huber Corporation

PO BOX 38

CRYSTAL HILL, VA

US 24539

Contact: Ted Hudson

ted.hudson@huber.com

T: (434)476-6628

F: (434)476-8133

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)