



VOLVO

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION



Machine Id
VOLVO L150H 6989
Component
Diesel Engine
Fluid
VALVOLINE 15W40 (--- GAL)

RECOMMENDATION

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP452636	VCP443834	VCP436472
Sample Date		Client Info		07 Jul 2024	13 Jun 2024	09 May 2024
Machine Age	hrs	Client Info		7460	7304	7072
Oil Age	hrs	Client Info		0	232	324
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	Changed	Changed
Sample Status				ATTENTION	ATTENTION	ATTENTION

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>200	2	0	7
Chromium	ppm	ASTM D5185m	>20	0	<1	2
Nickel	ppm	ASTM D5185m	>5	<1	0	3
Titanium	ppm	ASTM D5185m		0	0	2
Silver	ppm	ASTM D5185m	>2	0	0	3
Aluminum	ppm	ASTM D5185m	>30	2	2	5
Lead	ppm	ASTM D5185m	>40	<1	0	3
Copper	ppm	ASTM D5185m	>20	0	0	4
Tin	ppm	ASTM D5185m	>20	<1	0	3
Vanadium	ppm	ASTM D5185m		0	0	2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION













There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	4	5	10
Potassium	ppm	ASTM D5185m	>20	2	2	5
Fuel	%	ASTM D3524	>6.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	5.5	5.6	6.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	14.9	15.1	15.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The oil viscosity is lower than normal. The BN result indicates that there is suitable alkalinity remaining in the oil. Confirm oil type.

Sodium	ppm	ASTM D5185m		<1	<1	4
Boron	ppm	ASTM D5185m	39	71	46	46
Barium	ppm	ASTM D5185m	1	0	0	3
Molybdenum	ppm	ASTM D5185m	49	75	74	61
Manganese	ppm	ASTM D5185m	1	0	0	2
Magnesium	ppm	ASTM D5185m	616	254	220	228
Calcium	ppm	ASTM D5185m	1554	1795	1732	2340
Phosphorus	ppm	ASTM D5185m	899	875	706	985
Zinc	ppm	ASTM D5185m	1069	1049	951	1148
Sulfur	ppm	ASTM D5185m	2624	4055	2775	4123
Oxidation	Abs/.1mm	*ASTM D7414	>25	8.8	8.3	8.5
Base Number (BN)	mg KOH/g	ASTM D2896	6.9	6.7	6.1	6.5
Visc @ 100°C	cSt	ASTM D445	13.6	11.1	10.8	11.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VCP452636 **Received** : 12 Jul 2024
Lab Number : 06234408 **Tested** : 12 Jul 2024
Unique Number : 11123242 **Diagnosed** : 14 Jul 2024 - Don Baldridge
Test Package : MOB 1 (Additional Tests: FuelDilution, TBN)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

CITY CARTING
 221 OLD GATE LN
 MILFORD, CT
 US 06460
 Contact: TAVINS BANKS
 tavins@citycart.net
 T: (203)223-3885
 F: