



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area

[MH-19]

Machine Id

SENNEBOGEN 825-M MH-19 (S/N 825-0-1284)

Component

Diesel Engine

Fluid

DURALENE Dura-Max 15W40 (5 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		DC0033551	DC0033554	DC0028796
Sample Date		Client Info		21 Jun 2024	08 May 2024	18 Sep 2023
Machine Age	hrs	Client Info		18438	18314	17734
Oil Age	hrs	Client Info		124	580	680
Filter Age	hrs	Client Info		124	580	680
Oil Changed		Client Info		Not Changd	Changed	Changed
Filter Changed		Client Info		Not Changd	Changed	Changed
Sample Status				NORMAL	ATTENTION	ATTENTION

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	6	16	18
Chromium	ppm	ASTM D5185m	>20	3	6	5
Nickel	ppm	ASTM D5185m	>4	0	<1	0
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	2	3	1
Lead	ppm	ASTM D5185m	>40	0	2	2
Copper	ppm	ASTM D5185m	>330	1	3	4
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	2	3	4
Potassium	ppm	ASTM D5185m	>20	7	3	2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.2	0.5	0
Nitration	Abs/cm	*ASTM D7624	>20	5.7	6.0	6.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.0	22.0	26.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		11	<1	5
Boron	ppm	ASTM D5185m		3	1	2
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		4	2	2
Manganese	ppm	ASTM D5185m		0	<1	1
Magnesium	ppm	ASTM D5185m		49	24	34
Calcium	ppm	ASTM D5185m		2024	1576	1623
Phosphorus	ppm	ASTM D5185m		781	618	600
Zinc	ppm	ASTM D5185m		920	744	717
Sulfur	ppm	ASTM D5185m		3040	3230	3221
Oxidation	Abs/.1mm	*ASTM D7414	>25	11.6	14.2	16.6
Base Number (BN)	mg KOH/g	ASTM D2896		6.6	4.7	5.4
Visc @ 100°C	cSt	ASTM D445		12.6	● 11.8	● 11.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : DC0033551 **Received** : 12 Jul 2024
Lab Number : 06234559 **Tested** : 12 Jul 2024
Unique Number : 11123393 **Diagnosed** : 12 Jul 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

CONSERVIT INC.
 PO BOX 1517
 HAGERSTOWN, MD
 US 21740
 Contact: DON LONG

T: (301)791-0100
 F: (301)739-8548