



Machine Id
JOHN DEERE 130G C329972 (S/N 042024)
Component
Right Final Drive
Fluid
GEAR OIL SAE 80W90 (--- GAL)

RECOMMENDATION

We advise that you check all areas where dirt can enter the system. Oil and filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0218767	---	---
Sample Date		Client Info		14 Jul 2024	---	---
Machine Age	hrs	Client Info		3764	---	---
Oil Age	hrs	Client Info		3764	---	---
Filter Age	hrs	Client Info		3764	---	---
Oil Changed		Client Info		Changed	---	---
Filter Changed		Client Info		Changed	---	---
Sample Status				SEVERE	---	---

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	1788	---	---
Iron	ppm	ASTM D5185m	>750	5213	---	---
Chromium	ppm	ASTM D5185m	>9	50	---	---
Nickel	ppm	ASTM D5185m	>10	11	---	---
Titanium	ppm	ASTM D5185m		12	---	---
Silver	ppm	ASTM D5185m		0	---	---
Aluminum	ppm	ASTM D5185m	>40	115	---	---
Lead	ppm	ASTM D5185m	>15	0	---	---
Copper	ppm	ASTM D5185m	>40	15	---	---
Tin	ppm	ASTM D5185m	>10	0	---	---
Vanadium	ppm	ASTM D5185m		<1	---	---
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---

CONTAMINATION








Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress.

Silicon	ppm	ASTM D5185m	>75	1168	---	---
Potassium	ppm	ASTM D5185m	>20	24	---	---
Water		WC Method	>0.075	NEG	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.075	NEG	---	---

FLUID CONDITION

The oil is no longer serviceable due to the presence of contaminants.

Sodium	ppm	ASTM D5185m	>170	2	---	---
Boron	ppm	ASTM D5185m	400	52	---	---
Barium	ppm	ASTM D5185m	200	4	---	---
Molybdenum	ppm	ASTM D5185m	12	4	---	---
Manganese	ppm	ASTM D5185m		44	---	---
Magnesium	ppm	ASTM D5185m	12	14	---	---
Calcium	ppm	ASTM D5185m	150	185	---	---
Phosphorus	ppm	ASTM D5185m	1650	459	---	---
Zinc	ppm	ASTM D5185m	125	112	---	---
Sulfur	ppm	ASTM D5185m	22500	25825	---	---
Visc @ 40°C	cSt	ASTM D445	143	210	---	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0218767 **Received** : 12 Jul 2024
Lab Number : 06235179 **Tested** : 15 Jul 2024
Unique Number : 11124013 **Diagnosed** : 15 Jul 2024 - Sean Felton
Test Package : CONST (Additional Tests: PQ)

JRE - ASHEVILLE
 101 BRUCE DRIVE
 ASHEVILLE, NC
 US 28806

Contact: Randy Warren
 randy.warren@jamesriverequipment.com
 T: (528)667-0176
 F: (828)667-4865

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)