



OIL ANALYSIS REPORT

| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Area
AMR-Cheyenne
 Machine Id
439142 SENNEBOGEN 840E 840.0.2133
 Component
Front Left Planetary
 Fluid
CHEVRON DELO GEAR ESI OIL 80W90 (3 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | DJJ0023961 | DJJ0023242 | DJJ0019105 |
| Sample Date | | Client Info | | 24 Jun 2024 | 13 Mar 2024 | 05 Dec 2023 |
| Machine Age | hrs | Client Info | | 13360 | 12659 | 12141 |
| Oil Age | hrs | Client Info | | 500 | 1000 | 500 |
| Filter Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | Not Changed | Changed | Not Changed |
| Filter Changed | | Client Info | | Not Changed | N/A | N/A |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|--------------|------|------|
| Iron | ppm | ASTM D5185m | >500 | 15 | 54 | 36 |
| Chromium | ppm | ASTM D5185m | >10 | <1 | <1 | <1 |
| Nickel | ppm | ASTM D5185m | >10 | 0 | <1 | 0 |
| Titanium | ppm | ASTM D5185m | | <1 | <1 | <1 |
| Silver | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >25 | 3 | 2 | 3 |
| Lead | ppm | ASTM D5185m | >25 | 0 | 1 | 0 |
| Copper | ppm | ASTM D5185m | >75 | <1 | 1 | <1 |
| Tin | ppm | ASTM D5185m | >10 | 0 | 2 | 0 |
| Vanadium | ppm | ASTM D5185m | | <1 | 0 | 0 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION





There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|--------|-------------|-------|--------------|-------|-------|
| Silicon | ppm | ASTM D5185m | >75 | 2 | 8 | 3 |
| Potassium | ppm | ASTM D5185m | >20 | 1 | 1 | <1 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Silt | scalar | *Visual | NONE | NONE | MODER | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG | NEG |

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

| | | | | | | |
|-------------|-----|-------------|-------|--------------|-------|-------|
| Sodium | ppm | ASTM D5185m | | 0 | 2 | 0 |
| Boron | ppm | ASTM D5185m | 15 | 188 | 174 | 216 |
| Barium | ppm | ASTM D5185m | 0 | <1 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | 0 | 0 | <1 | <1 |
| Manganese | ppm | ASTM D5185m | | 0 | 1 | 0 |
| Magnesium | ppm | ASTM D5185m | 0 | <1 | 0 | <1 |
| Calcium | ppm | ASTM D5185m | 5 | 0 | 12 | 6 |
| Phosphorus | ppm | ASTM D5185m | 600 | 1050 | 1147 | 1158 |
| Zinc | ppm | ASTM D5185m | 0 | 2 | 3 | 0 |
| Sulfur | ppm | ASTM D5185m | 22000 | 17287 | 20946 | 21274 |
| Visc @ 40°C | cSt | ASTM D445 | 140 | 141 | 141 | 143 |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : DJJ0023961
Lab Number : 06235273
Unique Number : 11124107
Test Package : CONST

Received : 12 Jul 2024
Tested : 15 Jul 2024
Diagnosed : 15 Jul 2024 - Wes Davis

ADVANTAGE METALS RECYCLING - CHEYENNE
 1015 S. PACKARD ST
 KANSAS CITY, KS
 US 66105
 Contact: BRIAN JACOBS
 BRIAN.JACOBS@ADVANTAGERECYCLING.COM
 T: (816)808-4711
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)