



| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Machine Id
933024
 Component
Natural Gas Engine
 Fluid
PETRO CANADA DURON GEO LD 15W40 (--- LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | GFL0124072 | GFL0124046 | GFL0120148 |
| Sample Date | | Client Info | | 09 Jul 2024 | 17 Jun 2024 | 28 May 2024 |
| Machine Age | hrs | Client Info | | 3621 | 3444 | 3307 |
| Oil Age | hrs | Client Info | | 0 | 0 | 0 |
| Filter Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | Not Changd | Not Changd | Not Changd |
| Filter Changed | | Client Info | | Not Changd | Not Changd | Not Changd |
| Sample Status | | | | NORMAL | NORMAL | ABNORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|--------------|------|------|
| Iron | ppm | ASTM D5185m | >50 | 8 | 6 | ▲ 51 |
| Chromium | ppm | ASTM D5185m | >4 | 1 | <1 | 2 |
| Nickel | ppm | ASTM D5185m | >2 | 0 | 0 | 0 |
| Titanium | ppm | ASTM D5185m | | 0 | <1 | 0 |
| Silver | ppm | ASTM D5185m | >3 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >9 | 2 | 1 | 3 |
| Lead | ppm | ASTM D5185m | >30 | <1 | 2 | 0 |
| Copper | ppm | ASTM D5185m | >35 | 1 | <1 | 0 |
| Tin | ppm | ASTM D5185m | >4 | 0 | 0 | 0 |
| Vanadium | ppm | ASTM D5185m | | 0 | <1 | 0 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION








There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|----------|-------------|-------|--------------|-------|-------|
| Silicon | ppm | ASTM D5185m | >+100 | 27 | 4 | 14 |
| Potassium | ppm | ASTM D5185m | >20 | <1 | 2 | 0 |
| Water | | WC Method | >0.1 | NEG | NEG | NEG |
| Soot % | % | *ASTM D7844 | | 0 | 0 | 0.1 |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 11.0 | 7.9 | 7.2 |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 24.3 | 19.4 | 19.6 |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG | NEG |

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| | | | | | | |
|------------------|----------|-------------|------|--------------|------|------|
| Sodium | ppm | ASTM D5185m | | 7 | 6 | 5 |
| Boron | ppm | ASTM D5185m | 50 | 1 | 27 | 35 |
| Barium | ppm | ASTM D5185m | 5 | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | 50 | 50 | 50 | 48 |
| Manganese | ppm | ASTM D5185m | 0 | <1 | <1 | <1 |
| Magnesium | ppm | ASTM D5185m | 560 | 561 | 622 | 567 |
| Calcium | ppm | ASTM D5185m | 1510 | 1634 | 1776 | 1506 |
| Phosphorus | ppm | ASTM D5185m | 780 | 734 | 877 | 803 |
| Zinc | ppm | ASTM D5185m | 870 | 926 | 1087 | 929 |
| Sulfur | ppm | ASTM D5185m | 2040 | 2763 | 3163 | 2654 |
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 19.3 | 15.7 | 15.2 |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 10.2 | 3.5 | 7.5 | 7.8 |
| Visc @ 100°C | cSt | ASTM D445 | 15.1 | 13.8 | 14.4 | 14.2 |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0124072
Lab Number : 06235477
Unique Number : 11124311
Test Package : FLEET

Received : 15 Jul 2024
Tested : 15 Jul 2024
Diagnosed : 15 Jul 2024 - Wes Davis

GFL Environmental - 836 - Kansas City Hauling
 7801 East Truman Road
 Kansas City, MO
 US 64126
 Contact: Loyce Stewart
 loyce.stewart@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: