



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
CAPT RICKIE JOHNSON (S/N 74G1-1161)
Component
Port Main Engine
Fluid
CHEVRON DELO 710 LE (250 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		MW0044526	MWM731177	MWM727712
Sample Date		Client Info		04 Jul 2024	20 Mar 2024	03 Jan 2024
Machine Age	hrs	Client Info		47362	44899	43092
Oil Age	hrs	Client Info		21417	18930	17108
Filter Age	hrs	Client Info		37	0	0
Oil Changed		Client Info		Not Chngd	Not Chngd	Not Chngd
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	19	22	21
Chromium	ppm	ASTM D5185m	>8	1	<1	<1
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m	>3	<1	0	0
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>15	3	<1	2
Lead	ppm	ASTM D5185m	>18	2	1	<1
Copper	ppm	ASTM D5185m	>80	10	9	11
Tin	ppm	ASTM D5185m	>14	1	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	4	3	3
Potassium	ppm	ASTM D5185m	>20	142	111	97
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	1.4	1.6	1.7
Nitration	Abs/cm	*ASTM D7624	>20	7.9	8.3	8.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.1	17.6	18.0
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>75	26	19	16
Boron	ppm	ASTM D5185m		38	31	35
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		60	54	46
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		36	11	10
Calcium	ppm	ASTM D5185m		3379	3751	3344
Phosphorus	ppm	ASTM D5185m		48	14	46
Zinc	ppm	ASTM D5185m	10	36	6	0
Sulfur	ppm	ASTM D5185m		2471	3327	2916
Oxidation	Abs/.1mm	*ASTM D7414	>25	7.1	7.6	7.9
Base Number (BN)	mg KOH/g	ASTM D2896	9.2	7.4	8.0	7.4
Visc @ 100°C	cSt	ASTM D445	15.5	14.9	15.0	14.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : MW0044526
Lab Number : 06235516
Unique Number : 11124350
Test Package : MAR 2

Received : 15 Jul 2024
Tested : 15 Jul 2024
Diagnosed : 16 Jul 2024 - Don Baldridge

AMERICAN COMMERCIAL LINES
 PO BOX 610, 1701 E. MARKET STREET
 JEFFERSONVILLE, IN
 US 47130
 Contact: RONALD SCHNEIDER
 ronald.schneider@bargaeacbl.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
 F: (812)288-1644