



Machine Id
CAPT RICKIE JOHNSON (S/N PE6068G838012)
Component
Port Genset
Fluid
CHEVRON DELO 710 LE (8 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		MW0044529	MWM731168	MWM727715
Sample Date		Client Info		16 Jun 2024	18 Mar 2024	27 Dec 2023
Machine Age	hrs	Client Info		7000	5797	42895
Oil Age	hrs	Client Info		312	301	282
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	10	6	6
Chromium	ppm	ASTM D5185m	>4	1	0	<1
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>5	<1	0	0
Aluminum	ppm	ASTM D5185m	>12	3	<1	2
Lead	ppm	ASTM D5185m	>17	6	<1	0
Copper	ppm	ASTM D5185m	>70	2	0	1
Tin	ppm	ASTM D5185m	>15	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	2	2	3
Potassium	ppm	ASTM D5185m	>20	9	4	2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844		0.1	0.1	0.2
Nitration	Abs/cm	*ASTM D7624	>20	10.3	9.2	7.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	16.5	15.6	15.1
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		0	2	1
Boron	ppm	ASTM D5185m		37	32	45
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		47	39	41
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		9	11	11
Calcium	ppm	ASTM D5185m		3598	3554	3576
Phosphorus	ppm	ASTM D5185m		21	13	45
Zinc	ppm	ASTM D5185m	10	6	11	0
Sulfur	ppm	ASTM D5185m		2633	3271	3234
Oxidation	Abs/.1mm	*ASTM D7414	>25	11.4	10.1	8.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.2	6.8	7.5	7.0
Visc @ 100°C	cSt	ASTM D445	15.5	14.7	14.3	14.1


FT-IR (Direct Trend)




Base Number




Viscosity @ 100°C




Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : MW0044529

Lab Number : 06235518

Unique Number : 11124352

Test Package : MAR 2

Received : 15 Jul 2024

Tested : 15 Jul 2024

Diagnosed : 15 Jul 2024 - Wes Davis

AMERICAN COMMERCIAL LINES

PO BOX 610, 1701 E. MARKET STREET

JEFFERSONVILLE, IN

US 47130

Contact: RONALD SCHNEIDER

ronald.schneider@bargaeacbl.com

T:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (812)288-1644