



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JCB 550-80 257469 (S/N 2083965)
 Component
Transmission (Manual)
 Fluid
JCB EP 10 (5 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JCB005497	---	---
Sample Date		Client Info		10 Jul 2024	---	---
Machine Age	hrs	Client Info		9822	---	---
Oil Age	hrs	Client Info		4337	---	---
Filter Age	hrs	Client Info		4337	---	---
Oil Changed		Client Info		Changed	---	---
Filter Changed		Client Info		Changed	---	---
Sample Status				NORMAL	---	---

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>95	30	---	---
Iron	ppm	ASTM D5185m	>200	115	---	---
Chromium	ppm	ASTM D5185m	>5	<1	---	---
Nickel	ppm	ASTM D5185m	>5	<1	---	---
Titanium	ppm	ASTM D5185m		2	---	---
Silver	ppm	ASTM D5185m	>7	0	---	---
Aluminum	ppm	ASTM D5185m	>25	6	---	---
Lead	ppm	ASTM D5185m	>45	36	---	---
Copper	ppm	ASTM D5185m	>225	121	---	---
Tin	ppm	ASTM D5185m	>10	1	---	---
Vanadium	ppm	ASTM D5185m		0	---	---
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---

CONTAMINATION











There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>125	13	---	---
Potassium	ppm	ASTM D5185m	>20	3	---	---
Water		WC Method	>0.1	NEG	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.1	NEG	---	---

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		2	---	---
Boron	ppm	ASTM D5185m		68	---	---
Barium	ppm	ASTM D5185m		0	---	---
Molybdenum	ppm	ASTM D5185m		2	---	---
Manganese	ppm	ASTM D5185m		3	---	---
Magnesium	ppm	ASTM D5185m		22	---	---
Calcium	ppm	ASTM D5185m		3137	---	---
Phosphorus	ppm	ASTM D5185m		1112	---	---
Zinc	ppm	ASTM D5185m		1265	---	---
Sulfur	ppm	ASTM D5185m		3970	---	---
Visc @ 40°C	cSt	ASTM D445		36.4	---	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JCB005497 **Received** : 15 Jul 2024
Lab Number : 06236472 **Tested** : 17 Jul 2024
Unique Number : 11125306 **Diagnosed** : 17 Jul 2024 - Jonathan Hester
Test Package : MOB 1 (Additional Tests: PQ)

HOOBER INC
 43 INDUSTRIAL CIRCLE
 MIFFLINTOWN, PA
 US 17059
 Contact: RALPH SANER
 jhicks@hooper.com
 T: (717)463-4108
 F: (717)463-2312

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)