



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
(YA171054)
Machine Id
932030
Component
Natural Gas Engine
Fluid
{not provided} (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0123350	GFL0123417	GFL0082487
Sample Date		Client Info		11 Jul 2024	18 Jun 2024	14 Nov 2023
Machine Age	hrs	Client Info		1212	1212	1212
Oil Age	hrs	Client Info		1212	1212	1212
Filter Age	hrs	Client Info		1212	1212	1212
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	10	10	6
Chromium	ppm	ASTM D5185m	>4	<1	<1	<1
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>9	6	4	2
Lead	ppm	ASTM D5185m	>30	11	12	2
Copper	ppm	ASTM D5185m	>35	4	4	2
Tin	ppm	ASTM D5185m	>4	0	0	1
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>+100	7	7	12
Potassium	ppm	ASTM D5185m	>20	8	8	5
Water		WC Method	>0.1	NEG	NEG	NEG
Soot %	%	*ASTM D7844		0	0	0
Nitration	Abs/cm	*ASTM D7624	>20	12.3	12.0	11.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	26.8	26.2	24.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		11	10	6
Boron	ppm	ASTM D5185m		7	6	3
Barium	ppm	ASTM D5185m		0	<1	<1
Molybdenum	ppm	ASTM D5185m		54	56	55
Manganese	ppm	ASTM D5185m		<1	<1	1
Magnesium	ppm	ASTM D5185m		602	619	585
Calcium	ppm	ASTM D5185m		1795	1950	1572
Phosphorus	ppm	ASTM D5185m		815	858	740
Zinc	ppm	ASTM D5185m		1005	1107	965
Sulfur	ppm	ASTM D5185m		2810	3013	2343
Oxidation	Abs/.1mm	*ASTM D7414	>25	23.2	22.3	20.7
Base Number (BN)	mg KOH/g	ASTM D2896		3.4	3.5	3.5
Visc @ 100°C	cSt	ASTM D445		14.6	14.5	14.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0123350 **Received** : 16 Jul 2024
Lab Number : 06237531 **Tested** : 17 Jul 2024
Unique Number : 11126365 **Diagnosed** : 17 Jul 2024 - Wes Davis
Test Package : FLEET

GFL Environmental - 007 - Brunswick
 2809 Galloway Road
 Bolivia, NC
 US 28422
 Contact: DONALD CRAVEN
 dcraven@gflenv.com
 T:
 F: (910)253-4179

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)