



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
(P634972) 020
Machine Id
2570
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (54 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0126045	GFL0103777	GFL0091160
Sample Date		Client Info		12 Jul 2024	07 Mar 2024	24 Nov 2023
Machine Age	hrs	Client Info		24232	23773	23304
Oil Age	hrs	Client Info		600	469	600
Filter Age	hrs	Client Info		600	469	600
Oil Changed		Client Info		Changed	Not Changed	Changed
Filter Changed		Client Info		Changed	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	18	21	18
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>5	0	<1	0
Titanium	ppm	ASTM D5185m	>2	0	<1	0
Silver	ppm	ASTM D5185m	>2	0	<1	0
Aluminum	ppm	ASTM D5185m	>20	3	2	<1
Lead	ppm	ASTM D5185m	>40	1	3	<1
Copper	ppm	ASTM D5185m	>330	7	66	1
Tin	ppm	ASTM D5185m	>15	0	2	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	3	3	2
Potassium	ppm	ASTM D5185m	>20	32	2	<1
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>4	1.3	1.1	1.2
Nitration	Abs/cm	*ASTM D7624	>20	6.8	6.5	7.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.8	19.3	19.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		5	0	2
Boron	ppm	ASTM D5185m	0	5	5	10
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	59	62	58
Manganese	ppm	ASTM D5185m	0	0	<1	<1
Magnesium	ppm	ASTM D5185m	1010	919	945	818
Calcium	ppm	ASTM D5185m	1070	1074	1140	1007
Phosphorus	ppm	ASTM D5185m	1150	888	1125	910
Zinc	ppm	ASTM D5185m	1270	1206	1243	1073
Sulfur	ppm	ASTM D5185m	2060	2734	3360	2625
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.4	13.4	13.3
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.7	8.7	8.5
Visc @ 100°C	cSt	ASTM D445	15.4	14.0	13.7	13.0



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0126045 **Received** : 16 Jul 2024
Lab Number : 06237598 **Tested** : 17 Jul 2024
Unique Number : 11126432 **Diagnosed** : 17 Jul 2024 - Wes Davis
Test Package : FLEET

GFL Environmental - 020 - Alamance
 703 East Gilbreath St
 Graham, NC
 US 27253
 Contact:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

richard.belcher@gflenv.com

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (800)207-6618

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (336)229-0526