



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
EPIROC D60 G19SED0164
 Component
Diesel Engine
 Fluid
JOHN DEERE ENGINE OIL PLUS 50 II 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0222143	JR0212714	JR0209599
Sample Date		Client Info		10 Jul 2024	08 May 2024	08 Mar 2024
Machine Age	hrs	Client Info		9709	9475	9133
Oil Age	hrs	Client Info		234	9133	258
Filter Age	hrs	Client Info		234	0	258
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	15	14	19
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	4	4	4
Lead	ppm	ASTM D5185m	>40	1	3	3
Copper	ppm	ASTM D5185m	>330	2	2	4
Tin	ppm	ASTM D5185m	>15	0	0	0
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION








There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	9	8	10
Potassium	ppm	ASTM D5185m	>20	1	<1	0
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.5	0.5	0.4
Nitration	Abs/cm	*ASTM D7624	>20	9.1	9.1	9.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.1	22.3	23.0
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		1	2	2
Boron	ppm	ASTM D5185m		166	191	120
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		244	249	203
Manganese	ppm	ASTM D5185m		<1	<1	0
Magnesium	ppm	ASTM D5185m		892	861	703
Calcium	ppm	ASTM D5185m		1739	1583	1611
Phosphorus	ppm	ASTM D5185m		1019	954	929
Zinc	ppm	ASTM D5185m		1267	1160	1067
Sulfur	ppm	ASTM D5185m		4162	3659	3408
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.1	16.9	17.9
Base Number (BN)	mg KOH/g	ASTM D2896	13.6	8.4	8.2	7.5
Visc @ 100°C	cSt	ASTM D445	15.4	13.1	13.1	13.0



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0222143 **Received** : 16 Jul 2024
Lab Number : 06237638 **Tested** : 19 Jul 2024
Unique Number : 11126472 **Diagnosed** : 19 Jul 2024 - Wes Davis
Test Package : CONST (Additional Tests: TBN)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

GARNER - MARTIN MARIETTA
 1111 E GARNER RD
 GARNER, NC
 US 27529
 Contact: JASON GILMORE
 jason.gilmore@martinmarietta.com

T:
F: