



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**[48053]**  
Machine Id  
**JOHN DEERE 755K 1T0755KXEMF403799**  
Component  
**Right Inner Final Drive**  
Fluid  
**JOHN DEERE HY-GARD HYD/TRANS (12 QTS)**

### RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>JR0225482</b>	JR0203256	JR0182144
Sample Date		Client Info		<b>15 Jul 2024</b>	19 Feb 2024	27 Jul 2023
Machine Age	hrs	Client Info		<b>3402</b>	2923	2432
Oil Age	hrs	Client Info		<b>479</b>	2408	515
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Changd</b>	Changed	N/A
Filter Changed		Client Info		<b>N/A</b>	None	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

### WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	<b>16</b>	12	15
Iron	ppm	ASTM D5185m	>750	<b>5</b>	7	13
Chromium	ppm	ASTM D5185m	>9	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m		<b>0</b>	<1	0
Aluminum	ppm	ASTM D5185m	>40	<b>3</b>	<1	<1
Lead	ppm	ASTM D5185m	>15	<b>0</b>	0	0
Copper	ppm	ASTM D5185m	>40	<b>0</b>	<1	0
Tin	ppm	ASTM D5185m	>10	<b>0</b>	<1	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	MODER
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

### CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	<b>5</b>	3	3
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	0	0
Water		WC Method	>0.075	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>LIGHT</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	<b>NEG</b>	NEG	NEG

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	<b>0</b>	<1	<1
Boron	ppm	ASTM D5185m	6	<b>19</b>	4	6
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	0	<b>14</b>	4	4
Manganese	ppm	ASTM D5185m		<b>0</b>	<1	0
Magnesium	ppm	ASTM D5185m	145	<b>146</b>	82	113
Calcium	ppm	ASTM D5185m	3570	<b>3399</b>	3272	3601
Phosphorus	ppm	ASTM D5185m	1290	<b>897</b>	1009	1071
Zinc	ppm	ASTM D5185m	1640	<b>1259</b>	1199	1324
Sulfur	ppm	ASTM D5185m		<b>3328</b>	3287	4682
Visc @ 40°C	cSt	ASTM D445	57.0	<b>50.6</b>	51.5	52.3



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : JR0225482 **Received** : 16 Jul 2024  
**Lab Number** : 06238093 **Tested** : 17 Jul 2024  
**Unique Number** : 11126927 **Diagnosed** : 17 Jul 2024 - Wes Davis  
**Test Package** : CONST ( Additional Tests: PQ )

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**CWS-STRITTMATTER**  
 9102 OWENS DR  
 MANASSAS PARK, VA  
 US 20111

Contact: EDDIE GARRETSON  
 egarretson@strittmattercompanies.com

T: (703)335-2255

F: (703)335-8095