



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
[05W48197]
 Machine Id
JOHN DEERE 250G B-140 (S/N 1FF250GXLLF611665)
 Component
Right Final Drive
 Fluid
JOHN DEERE GL-5 80W90 (8 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0226711	JR0196049	JR0122828
Sample Date		Client Info		15 Jul 2024	08 Jan 2024	29 Mar 2022
Machine Age	hrs	Client Info		9827	8015	2330
Oil Age	hrs	Client Info		1800	8015	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	N/A	Not Changd
Filter Changed		Client Info		N/A	N/A	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	29	52	102
Iron	ppm	ASTM D5185m	>750	25	49	77
Chromium	ppm	ASTM D5185m	>9	<1	<1	3
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>40	3	0	<1
Lead	ppm	ASTM D5185m	>15	0	0	<1
Copper	ppm	ASTM D5185m	>40	<1	<1	<1
Tin	ppm	ASTM D5185m	>10	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	3	6	11
Potassium	ppm	ASTM D5185m	>20	<1	0	<1
Water		WC Method	>0.075	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	0	0	<1
Boron	ppm	ASTM D5185m		12	19	62
Barium	ppm	ASTM D5185m		0	1	0
Molybdenum	ppm	ASTM D5185m		<1	0	<1
Manganese	ppm	ASTM D5185m		0	2	4
Magnesium	ppm	ASTM D5185m		5	0	0
Calcium	ppm	ASTM D5185m		61	9	8
Phosphorus	ppm	ASTM D5185m		283	394	473
Zinc	ppm	ASTM D5185m		23	15	4
Sulfur	ppm	ASTM D5185m		16550	17086	12527
Visc @ 40°C	cSt	ASTM D445		139	153	189



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0226711 **Received** : 16 Jul 2024
Lab Number : **06238113** **Tested** : 17 Jul 2024
Unique Number : 11126947 **Diagnosed** : 18 Jul 2024 - Don Baldrige
Test Package : CONST (Additional Tests: PQ)

C & D RECOVERY
 24024 FREDERICK RD
 CLARKSBURG, MD
 US 20871
 Contact: HERBIE TRENT

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: