



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**JOHN DEERE 624 P 1DW624PAKPLZ17188**

Component  
**Hydraulic System**

Fluid  
**JOHN DEERE HYDRAU (--- GAL)**

### RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>JR0225125</b>	JR0164515	---
Sample Date		Client Info		<b>15 Jul 2024</b>	18 Jul 2023	---
Machine Age	hrs	Client Info		<b>1213</b>	456	---
Oil Age	hrs	Client Info		<b>1213</b>	0	---
Filter Age	hrs	Client Info		<b>1213</b>	0	---
Oil Changed		Client Info		<b>Not Chngd</b>	Not Chngd	---
Filter Changed		Client Info		<b>Not Chngd</b>	Not Chngd	---
Sample Status				<b>NORMAL</b>	NORMAL	---

### WEAR

All component wear rates are normal.

PQ	UOM	Method	Limit/Abn	Current	History1	History2
PQ		ASTM D8184		<b>16</b>	14	---
Iron	ppm	ASTM D5185m	>20	<b>2</b>	<1	---
Chromium	ppm	ASTM D5185m	>10	<b>2</b>	1	---
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	0	---
Titanium	ppm	ASTM D5185m		<b>0</b>	0	---
Silver	ppm	ASTM D5185m		<b>0</b>	0	---
Aluminum	ppm	ASTM D5185m	>10	<b>0</b>	0	---
Lead	ppm	ASTM D5185m	>10	<b>0</b>	<1	---
Copper	ppm	ASTM D5185m	>75	<b>&lt;1</b>	<1	---
Tin	ppm	ASTM D5185m	>10	<b>0</b>	0	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	---
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	---

### CONTAMINATION











The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Silicon	ppm	ASTM D5185m	>20	<b>1</b>	1	---
Potassium	ppm	ASTM D5185m	>20	<b>1</b>	2	---
Water		WC Method	>0.1	<b>NEG</b>	NEG	---
Particles >4µm		ASTM D7647	>5000	<b>689</b>	754	---
Particles >6µm		ASTM D7647	>1300	<b>145</b>	176	---
Particles >14µm		ASTM D7647	>160	<b>13</b>	16	---
Particles >21µm		ASTM D7647	>40	<b>2</b>	5	---
Particles >38µm		ASTM D7647	>10	<b>0</b>	0	---
Particles >71µm		ASTM D7647	>3	<b>0</b>	0	---
Oil Cleanliness		ISO 4406 (c)	>19/17/14	<b>17/14/11</b>	17/15/11	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	---
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	---

### FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>3</b>	1	---
Boron	ppm	ASTM D5185m		<b>0</b>	0	---
Barium	ppm	ASTM D5185m		<b>0</b>	2	---
Molybdenum	ppm	ASTM D5185m		<b>0</b>	<1	---
Manganese	ppm	ASTM D5185m		<b>0</b>	0	---
Magnesium	ppm	ASTM D5185m		<b>8</b>	2	---
Calcium	ppm	ASTM D5185m	87	<b>98</b>	98	---
Phosphorus	ppm	ASTM D5185m	727	<b>661</b>	639	---
Zinc	ppm	ASTM D5185m	900	<b>862</b>	841	---
Sulfur	ppm	ASTM D5185m	1500	<b>1987</b>	1726	---
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	<b>0.58</b>	0.80	---
Visc @ 40°C	cSt	ASTM D445	65	<b>59.0</b>	59.7	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
 Sample No. : JR0225125 Received : 17 Jul 2024  
 Lab Number : 06239028 Tested : 18 Jul 2024  
 Unique Number : 11127862 Diagnosed : 18 Jul 2024 - Wes Davis  
 Test Package : CONST ( Additional Tests: PQ )

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**JRE - ASHLAND**  
 11047 LEADBETTER RD  
 ASHLAND, VA  
 US 23005  
 Contact: DAVID ZIEG  
 dzieg@jamesriverequipment.com  
 T: (804)798-6001  
 F: (804)798-0292