



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[48107]
 Machine Id
JOHN DEERE 310E 1DW310EXJPF716428
 Component
Transmission (Auto)
 Fluid
JOHN DEERE HD SynTran (16 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0225773	JR0211178	JR0192313
Sample Date		Client Info		16 Jul 2024	10 Apr 2024	08 Nov 2023
Machine Age	hrs	Client Info		2465	1950	1475
Oil Age	hrs	Client Info		515	1950	1475
Filter Age	hrs	Client Info		0	1950	0
Oil Changed		Client Info		Not Changed	Changed	N/A
Filter Changed		Client Info		Not Changed	Changed	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>50	22	26	29
Iron	ppm	ASTM D5185m	>160	43	61	43
Chromium	ppm	ASTM D5185m	>5	<1	<1	0
Nickel	ppm	ASTM D5185m	>5	<1	<1	<1
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>50	3	1	<1
Lead	ppm	ASTM D5185m	>50	2	5	4
Copper	ppm	ASTM D5185m	>225	2	3	2
Tin	ppm	ASTM D5185m	>10	<1	1	0
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>20	3	4	4
Potassium	ppm	ASTM D5185m	>20	3	4	3
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		0	1	3
Boron	ppm	ASTM D5185m	168	120	129	124
Barium	ppm	ASTM D5185m		1	2	0
Molybdenum	ppm	ASTM D5185m		2	3	<1
Manganese	ppm	ASTM D5185m		<1	2	<1
Magnesium	ppm	ASTM D5185m		6	8	6
Calcium	ppm	ASTM D5185m	33	74	186	126
Phosphorus	ppm	ASTM D5185m	330	249	295	268
Zinc	ppm	ASTM D5185m	0	34	48	25
Sulfur	ppm	ASTM D5185m	980	326	472	495
Visc @ 40°C	cSt	ASTM D445	39	37.5	37.1	37.1



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0225773
Lab Number : 06239338
Unique Number : 11128172
Test Package : CONST (Additional Tests: PQ)

JRE - MANASSAS PARK
 9107 OWENS DRIVE
 MANASSAS PARK, VA
 US 20111
 Contact: DON VEST
 dvest@jamesriverequipment.com
 T: (703)631-8500
 F: (703)631-4715

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)