



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	ABNORMAL
FLUID CONDITION	NORMAL

Area
Shredder
Machine Id
ORU (Oil Recirculate Unit)-Shredder
Component
Hydraulic Power Pack
Fluid
SHELL HYDRAULIC S1 M 68 (--- GAL)

RECOMMENDATION

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		PE0001508	PE0002219	PE0003612
Sample Date		Client Info		10 Jul 2024	20 May 2024	18 Apr 2024
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL

WEAR

All component wear rates are normal.

PQ	UOM	Method	Limit/Abn	Current	History1	History2
PQ		ASTM D8184		23	17	24
Iron	ppm	ASTM D5185m	>20	8	4	8
Chromium	ppm	ASTM D5185m	>20	0	0	<1
Nickel	ppm	ASTM D5185m	>20	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>20	0	0	3
Lead	ppm	ASTM D5185m	>20	0	0	<1
Copper	ppm	ASTM D5185m	>20	2	1	3
Tin	ppm	ASTM D5185m	>20	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is a high amount of silt (particulates < 14 microns in size) present in the oil.

Silicon	ppm	ASTM D5185m	>15	<1	<1	1
Potassium	ppm	ASTM D5185m	>20	0	<1	2
Water		WC Method	>0.05	NEG	NEG	NEG
Particles >4µm		ASTM D7647	>5000	▲ 89318	▲ 26303	▲ 38171
Particles >6µm		ASTM D7647	>1300	▲ 17138	1199	● 1930
Particles >14µm		ASTM D7647	>160	62	2	8
Particles >21µm		ASTM D7647	>40	8	1	2
Particles >38µm		ASTM D7647	>10	1	0	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	▲ 24/21/13	▲ 22/17/9	▲ 22/18/10
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		1	<1	0
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	<1
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		2	2	4
Calcium	ppm	ASTM D5185m		73	70	39
Phosphorus	ppm	ASTM D5185m		344	341	318
Zinc	ppm	ASTM D5185m		429	415	377
Sulfur	ppm	ASTM D5185m		1437	1481	830
Acid Number (AN)	mg KOH/g	ASTM D8045		0.36	0.31	0.38
Visc @ 40°C	cSt	ASTM D445	68	63.8	65.3	65.9



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PE0001508 **Received** : 17 Jul 2024
Lab Number : 06239552 **Tested** : 18 Jul 2024
Unique Number : 11128386 **Diagnosed** : 19 Jul 2024 - Don Baldridge
Test Package : PLANT (Additional Tests: ICP, KV40, PQ, PrtCount, SCREEN)
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Seattle Iron and Metals
 601 S MYRTLE ST
 SEATTLE, WA
 US 98108
 Contact: ADAM THOMAS
 athomas@seairon.com
 T: (206)682-0040
 F: