



OIL ANALYSIS REPORT

| | |
|-----------------|--------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Machine Id
DFGS 273148
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number | | Client Info | | WC0950026 | WC0839036 | WC0708195 |
| Sample Date | | Client Info | | 11 Jun 2024 | 21 Jul 2023 | 20 Jul 2022 |
| Machine Age | hrs | Client Info | | 13813 | 0 | 11000 |
| Oil Age | hrs | Client Info | | 0 | 0 | 0 |
| Filter Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | N/A | Changed | N/A |
| Filter Changed | | Client Info | | N/A | Changed | N/A |
| Sample Status | | | | NORMAL | NORMAL | ABNORMAL |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|--------------|------|------|
| Iron | ppm | ASTM D5185m | >100 | 9 | 10 | 29 |
| Chromium | ppm | ASTM D5185m | >20 | 0 | <1 | 1 |
| Nickel | ppm | ASTM D5185m | >4 | 0 | 0 | <1 |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | <1 |
| Silver | ppm | ASTM D5185m | >3 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >20 | 5 | 4 | 10 |
| Lead | ppm | ASTM D5185m | >40 | 0 | <1 | 1 |
| Copper | ppm | ASTM D5185m | >330 | 1 | 1 | 4 |
| Tin | ppm | ASTM D5185m | >15 | <1 | <1 | <1 |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |

CONTAMINATION








There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon | ppm | ASTM D5185m | >25 | 4 | 4 | 7 |
| Potassium | ppm | ASTM D5185m | >20 | 2 | 2 | 5 |
| Fuel | | WC Method | >5 | <1.0 | <1.0 | <1.0 |
| Water | | WC Method | >0.2 | NEG | NEG | NEG |
| Glycol | | WC Method | | NEG | NEG | NEG |
| Soot % | % | *ASTM D7844 | >3 | 0.1 | 0.1 | 0.1 |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 8.7 | 8.3 | 11.1 |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 21.8 | 21.8 | 23.4 |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG | NEG |

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| | | | | | | |
|------------------|----------|-------------|------|-------------|------|-------|
| Sodium | ppm | ASTM D5185m | >158 | 51 | 83 | ▲ 985 |
| Boron | ppm | ASTM D5185m | 250 | 352 | 375 | 394 |
| Barium | ppm | ASTM D5185m | 10 | 0 | 2 | 0 |
| Molybdenum | ppm | ASTM D5185m | 100 | 80 | 91 | 86 |
| Manganese | ppm | ASTM D5185m | | 0 | <1 | <1 |
| Magnesium | ppm | ASTM D5185m | 450 | 351 | 417 | 356 |
| Calcium | ppm | ASTM D5185m | 3000 | 1901 | 1585 | 1544 |
| Phosphorus | ppm | ASTM D5185m | 1150 | 1043 | 1005 | 970 |
| Zinc | ppm | ASTM D5185m | 1350 | 1321 | 1244 | 1228 |
| Sulfur | ppm | ASTM D5185m | 4250 | 3823 | 3313 | 3437 |
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 17.2 | 17.3 | 18.7 |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 8.5 | 7.8 | 8.3 | 8.1 |
| Visc @ 100°C | cSt | ASTM D445 | 14.4 | 13.8 | 13.5 | 13.4 |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0950026
Lab Number : 06239792
Unique Number : 11128626
Test Package : FLEET

Received : 17 Jul 2024
Tested : 18 Jul 2024
Diagnosed : 18 Jul 2024 - Wes Davis

DOLE FRESH FRUIT
 PO BOX 725, ATTN: MAINTENANCE AND REPAIR
 NEW CASTLE, DE
 US 19720

Contact: LUIS LAPIERRE
 luis.lapierre@dole.com
 T: (302)652-6344
 F: (302)652-6061

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)