



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
LIEBHERR 22669
 Component
Diesel Engine
 Fluid
LIEBHERR MOTOROIL 10W-40 LOW ASH (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0950655	WC0913766	WC0856953
Sample Date		Client Info		15 Jul 2024	25 Mar 2024	01 Oct 2023
Machine Age	hrs	Client Info		5902	5470	4945
Oil Age	hrs	Client Info		1000	500	250
Filter Age	hrs	Client Info		1000	500	250
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	2	2	4
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m	>3	<1	0	<1
Aluminum	ppm	ASTM D5185m	>20	4	1	2
Lead	ppm	ASTM D5185m	>40	0	0	0
Copper	ppm	ASTM D5185m	>330	1	0	<1
Tin	ppm	ASTM D5185m	>15	<1	<1	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	6	6	9
Potassium	ppm	ASTM D5185m	>20	2	<1	0
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	10.1	9.3	9.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.0	20.4	18.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		0	<1	1
Boron	ppm	ASTM D5185m	169	128	150	321
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	2	42	24	44
Manganese	ppm	ASTM D5185m	<1	0	<1	<1
Magnesium	ppm	ASTM D5185m	724	853	749	303
Calcium	ppm	ASTM D5185m	1323	1424	1405	2541
Phosphorus	ppm	ASTM D5185m	678	772	750	1037
Zinc	ppm	ASTM D5185m	776	940	879	1199
Sulfur	ppm	ASTM D5185m	2859	2652	3333	3171
Oxidation	Abs/.1mm	*ASTM D7414	>25	21.6	20.4	14.7
Base Number (BN)	mg KOH/g	ASTM D2896	9.28	9.8	9.6	9.8
Visc @ 100°C	cSt	ASTM D445	13.0	14.1	12.8	13.3


FT-IR (Direct Trend)




Ferrous Alloys




Base Number




Viscosity @ 100°C




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : WC0950655

Lab Number : 06239900

Unique Number : 11128734

Test Package : CONST (Additional Tests: TBN)

Received : 18 Jul 2024

Tested : 18 Jul 2024

Diagnosed : 18 Jul 2024 - Wes Davis

SULLIVAN EASTERN INC-LIEBHERR

2860 C SLATER RD

MORRISVILLE, NC

US 27560

Contact: CHRIS CALTON

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (919)484-2136

F: (919)484-2136