



# OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id  
**PETERBILT ASL-10**  
Component  
**Diesel Engine**  
Fluid  
**GIBRALTAR 15W/40 SUPER S-3 LX (--- GAL)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>WC0941052</b>	WC0875381	---
Sample Date		Client Info		<b>02 Jul 2024</b>	18 Apr 2024	---
Machine Age	hrs	Client Info		<b>14780</b>	14155	---
Oil Age	hrs	Client Info		<b>600</b>	0	---
Filter Age	hrs	Client Info		<b>600</b>	0	---
Oil Changed		Client Info		<b>Changed</b>	Changed	---
Filter Changed		Client Info		<b>Changed</b>	Changed	---
Sample Status				<b>NORMAL</b>	NORMAL	---

## WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>110	<b>17</b>	35	---
Chromium	ppm	ASTM D5185m	>4	<b>1</b>	2	---
Nickel	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	---
Titanium	ppm	ASTM D5185m		<b>0</b>	<1	---
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	---
Aluminum	ppm	ASTM D5185m	>25	<b>3</b>	8	---
Lead	ppm	ASTM D5185m	>45	<b>5</b>	6	---
Copper	ppm	ASTM D5185m	>85	<b>5</b>	20	---
Tin	ppm	ASTM D5185m	>4	<b>0</b>	2	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	---
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	---

## CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>30	<b>5</b>	9	---
Potassium	ppm	ASTM D5185m	>20	<b>10</b>	15	---
Fuel		WC Method	>5	<b>&lt;1.0</b>	<1.0	---
Water		WC Method	>0.2	<b>NEG</b>	NEG	---
Glycol		WC Method		<b>NEG</b>	NEG	---
Soot %	%	*ASTM D7844	>3	<b>0.5</b>	0.8	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.5</b>	9.4	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>20.8</b>	21.0	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	---
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	---

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>3</b>	2	---
Boron	ppm	ASTM D5185m		<b>6</b>	8	---
Barium	ppm	ASTM D5185m		<b>0</b>	0	---
Molybdenum	ppm	ASTM D5185m	66	<b>66</b>	110	---
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	1	---
Magnesium	ppm	ASTM D5185m	1000	<b>814</b>	1098	---
Calcium	ppm	ASTM D5185m	1050	<b>1246</b>	1532	---
Phosphorus	ppm	ASTM D5185m	1150	<b>992</b>	1303	---
Zinc	ppm	ASTM D5185m	1270	<b>1138</b>	1610	---
Sulfur	ppm	ASTM D5185m		<b>3152</b>	4333	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>17.0</b>	16.7	---
Base Number (BN)	mg KOH/g	ASTM D2896	10.1	<b>7.1</b>	7.5	---
Visc @ 100°C	cSt	ASTM D445	15.5	<b>13.8</b>	13.5	---



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0941052 **Received** : 18 Jul 2024  
**Lab Number** : 06239941 **Tested** : 18 Jul 2024  
**Unique Number** : 11128775 **Diagnosed** : 18 Jul 2024 - Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**OAKRIDGE WASTE**  
 307 WHITE ST  
 DANBURY, CT  
 US 06810

Contact: CHRIS CONTI  
 chris.conti@oakridgewaste.com

T:  
 F: