



# ASCENDUM

## OIL ANALYSIS REPORT

WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**Ascendum Machinery/500 Hour CSA**  
Machine Id  
**VOLVO A45G 2363 (S/N A45GV752172)**  
Component  
**Bogie/Center Axle**  
Fluid  
**{not provided} (--- GAL)**

### RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>ASC0009419</b>	ASC0010300	---
Sample Date		Client Info		<b>16 Jul 2024</b>	02 Apr 2024	---
Machine Age	hrs	Client Info		<b>1058</b>	476	---
Oil Age	hrs	Client Info		<b>1058</b>	476	---
Filter Age	hrs	Client Info		<b>0</b>	0	---
Oil Changed		Client Info		<b>Changed</b>	Not Changd	---
Filter Changed		Client Info		<b>N/A</b>	N/A	---
Sample Status				<b>NORMAL</b>	NORMAL	---

### WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>900	<b>0</b>	150	---
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	3	---
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	1	---
Titanium	ppm	ASTM D5185m		<b>0</b>	<1	---
Silver	ppm	ASTM D5185m		<b>0</b>	2	---
Aluminum	ppm	ASTM D5185m	>30	<b>1</b>	3	---
Lead	ppm	ASTM D5185m	>50	<b>0</b>	1	---
Copper	ppm	ASTM D5185m	>150	<b>0</b>	2	---
Tin	ppm	ASTM D5185m	>20	<b>0</b>	1	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	---
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	---

### CONTAMINATION





There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>50	<b>&lt;1</b>	4	---
Potassium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	5	---
Water		WC Method	>0.2	<b>NEG</b>	NEG	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	---
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	---

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>&lt;1</b>	4	---
Boron	ppm	ASTM D5185m		<b>326</b>	246	---
Barium	ppm	ASTM D5185m		<b>0</b>	2	---
Molybdenum	ppm	ASTM D5185m		<b>0</b>	5	---
Manganese	ppm	ASTM D5185m		<b>0</b>	8	---
Magnesium	ppm	ASTM D5185m		<b>3</b>	3	---
Calcium	ppm	ASTM D5185m		<b>0</b>	118	---
Phosphorus	ppm	ASTM D5185m		<b>2300</b>	2012	---
Zinc	ppm	ASTM D5185m		<b>7</b>	58	---
Sulfur	ppm	ASTM D5185m		<b>25948</b>	22797	---
Visc @ 40°C	cSt	ASTM D445		<b>52.3</b>	52.3	---



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : ASC0009419  
**Lab Number** : 06240707  
**Unique Number** : 11129541  
**Test Package** : CONST

**Received** : 18 Jul 2024  
**Tested** : 19 Jul 2024  
**Diagnosed** : 19 Jul 2024 - Wes Davis

**G S MATERIALS INC**  
 PO BOX 1335  
 BURLINGTON, NC  
 US 27216

Contact: KAREN NEWPORT  
 Gsmaterials@windstream.net

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (919)499-9322  
 F: (919)499-2097