



Secteur
MICHAUDVILLE

Identité de la machine

1598

Composant

Moteur diesel

Fluide

PETRO CANADA DURON SHP 10W30 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Numéro d'échant.		Client Info		PC0072204	PC0072340	PC0067151
Date d'échant.		Client Info		06 Jul 2023	10 May 2023	17 Nov 2022
Âge d la Machine	hrs	Client Info		25561	25293	0
Âge de l'huile	hrs	Client Info		0	0	0
Âge du filtre	hrs	Client Info		0	0	0
Huile changée		Client Info		N/A	N/A	N/A
Filtre changé		Client Info		N/A	N/A	N/A
Statut de l'échant.				NORMAL	NORMAL	NORMAL

USURE

All component wear rates are normal.

Fer	ppm	ASTM D5185(m)	>100	5	8	9
Chrome	ppm	ASTM D5185(m)	>20	<1	<1	<1
Nickel	ppm	ASTM D5185(m)	>4	0	<1	0
Titane	ppm	ASTM D5185(m)		0	<1	<1
Argent	ppm	ASTM D5185(m)	>3	0	0	0
Aluminium	ppm	ASTM D5185(m)	>20	1	2	2
Plomb	ppm	ASTM D5185(m)	>40	<1	1	2
Cuivre	ppm	ASTM D5185(m)	>330	<1	<1	<1
Étain	ppm	ASTM D5185(m)	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION











There is no indication of any contamination in the oil.

Silicium	ppm	ASTM D5185(m)	>25	6	6	7
Potassium	ppm	ASTM D5185(m)	>20	<1	<1	<1
Essence		WC Method	>5	<1.0	<1.0	<1.0
Glycol		WC Method		NEG	NEG	NEG
% de suie	%	ASTM D7844*	>3	0	0.1	0
Nitration	Abs/cm	ASTM D7624*	>20	6.7	7.8	8.3
Sulfatation	Abs/.1mm	ASTM D7415*	>30	20.6	20.1	21.4
Eau émulsifiée	scalar	Visual*	>0.2	NEG	NEG	NEG

ÉTAT DU FLUIDE

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		3	4	4
Bore	ppm	ASTM D5185(m)	2	1	2	2
Baryum	ppm	ASTM D5185(m)	0	0	0	0
Molybdène	ppm	ASTM D5185(m)	50	55	60	57
Manganèse	ppm	ASTM D5185(m)	0	<1	<1	<1
Magnésium	ppm	ASTM D5185(m)	950	909	979	931
Calcium	ppm	ASTM D5185(m)	1050	1180	1152	1131
Phosphore	ppm	ASTM D5185(m)	995	1100	1109	1069
Zinc	ppm	ASTM D5185(m)	1180	1188	1216	1182
Soufre	ppm	ASTM D5185(m)	2600	2673	2760	2600
Oxydation	Abs/.1mm	ASTM D7414*	>25	15.8	15.7	16.6
Visc 40°C	cSt	ASTM D7279(m)	80.1	86.2	85.7	85.7
Visc 100°C	cSt	ASTM D7279(m)	12.00	13.1	12.8	12.8
Indice de viscosité (VI)	Scale	ASTM D2270*	144	152	147	147



ISO 17025:2017
Accredited
Laboratory

Laboratoire : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **LES ENTREPRISES MICHAUDVILLE INC.**
N° d'échantillon : PC0072204 **Reçu** : 07 Jul 2023
N° de laboratoire : 02568474 **Diagnostiqué** : 07 Jul 2023
Numéro unique : 5605520 **Diagnostiqueur** : Wes Davis
Analyse : MOB 1 (Additional Tests: KV40, VI)

Pour discuter ce rapport, contacter le service à la clientèle au 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

270 RUE BRUNET
 MONT ST-HILAIRE, QC
 CA J3H 0M6
 Contact: Martin Trudel
 mtrudel@michaudville.com

T:
 F: