



RAPPORT D'ANALYSE D'HUILE

USURE	NORMAL
CONTAMINATION	NORMAL
ÉTAT DU FLUIDE	NORMAL

Secteur

EQUIPMENTS GM [E26062023A]

Identité de la machine

SANY STH1056 1125 (S/N TH1056CD0117)

Composant

Système hydraulique Pré-rinçage

Fluide

SAE 5W30 (10 LTR)

RECOMMANDATION

Il s'agit du relevé de base de l'échantillon soumis.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Numéro d'échant.		Client Info		WC	---	---
Date d'échant.		Client Info		07 Apr 2023	---	---
Âge d la Machine	hrs	Client Info		65	---	---
Âge de l'huile	hrs	Client Info		0	---	---
Âge du filtre	hrs	Client Info		0	---	---
Huile changée		Client Info		N/A	---	---
Filtre changé		Client Info		N/A	---	---
Statut de l'échant.				NORMAL	---	---

USURE

{sans objet}

Fer	ppm	ASTM D5185(m)	>20	17	---	---
Chrome	ppm	ASTM D5185(m)	>10	<1	---	---
Nickel	ppm	ASTM D5185(m)	>10	0	---	---
Titane	ppm	ASTM D5185(m)		0	---	---
Argent	ppm	ASTM D5185(m)		0	---	---
Aluminium	ppm	ASTM D5185(m)	>10	2	---	---
Plomb	ppm	ASTM D5185(m)	>10	0	---	---
Cuivre	ppm	ASTM D5185(m)	>75	6	---	---
Étain	ppm	ASTM D5185(m)	>10	0	---	---
Vanadium	ppm	ASTM D5185(m)		0	---	---
Métal blanc	scalar	Visual*	NONE	NONE	---	---
Bronze	scalar	Visual*	NONE	NONE	---	---

CONTAMINATION











{sans objet}

Silicium	ppm	ASTM D5185(m)	>20	16	---	---
Potassium	ppm	ASTM D5185(m)	>20	2	---	---
Limon	scalar	Visual*	NONE	NONE	---	---
Débris	scalar	Visual*	NONE	NONE	---	---
Saleté	scalar	Visual*	NONE	NONE	---	---
Apparence	scalar	Visual*	NORML	NORML	---	---
Odeur	scalar	Visual*	NORML	NORML	---	---
Eau émulsifiée	scalar	Visual*	>0.1	NEG	---	---

ÉTAT DU FLUIDE

{sans objet}

Sodium	ppm	ASTM D5185(m)		6	---	---
Bore	ppm	ASTM D5185(m)		53	---	---
Baryum	ppm	ASTM D5185(m)		17	---	---
Molybdène	ppm	ASTM D5185(m)		56	---	---
Manganèse	ppm	ASTM D5185(m)		2	---	---
Magnésium	ppm	ASTM D5185(m)		1064	---	---
Calcium	ppm	ASTM D5185(m)		865	---	---
Phosphore	ppm	ASTM D5185(m)		1081	---	---
Zinc	ppm	ASTM D5185(m)		1147	---	---
Soufre	ppm	ASTM D5185(m)		2862	---	---
Visc 40°C	cSt	ASTM D7279(m)	60.0	83.7	---	---
Visc 100°C	cSt	ASTM D7279(m)	11.0	13.5	---	---
Indice de viscosité (VI)	Scale	ASTM D2270*	177	164	---	---



ISO 17025:2017
Accredited
Laboratory

Laboratoire : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
N° d'échantillon : WC **Reçu** : 07 Jul 2023
N° de laboratoire : 02568587 **Diagnostiqué** : 11 Jul 2023
Numéro unique : 5605633 **Diagnostiqueur** : Bill Quesnel
Analyse : MOB 1 (Additional Tests: KV100, KV40, Spat, VI)

Pour discuter ce rapport, contacter le service à la clientèle au 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

Envirolin Canada

520 rue Adanac
Quebec, QC
CA G1C 7B7

Contact: Patrick Levesque
patrick.levesque@envirolin.com

T: (418)623-1216
F: (418)660-8889