



USURE	NORMAL
CONTAMINATION	NORMAL
ÉTAT DU FLUIDE	NORMAL

Secteur
MICHAUDVILLE

Identité de la machine

7508

Composant

Moteur diesel

Fluide

DIESEL ENGINE OIL SAE 10W30 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Numéro d'échant.		Client Info		PC0077605	PC0065729	PC0053279
Date d'échant.		Client Info		16 Jul 2023	01 Sep 2022	05 Oct 2021
Âge d la Machine	hrs	Client Info		9578	11100	10813
Âge de l'huile	hrs	Client Info		0	0	0
Âge du filtre	hrs	Client Info		0	0	0
Huile changée		Client Info		N/A	N/A	N/A
Filtre changé		Client Info		N/A	N/A	N/A
Statut de l'échant.				NORMAL	NORMAL	NORMAL

USURE

All component wear rates are normal.

Fer	ppm	ASTM D5185(m)	>100	13	16	18
Chrome	ppm	ASTM D5185(m)	>20	<1	<1	<1
Nickel	ppm	ASTM D5185(m)	>4	0	0	<1
Titane	ppm	ASTM D5185(m)		0	<1	0
Argent	ppm	ASTM D5185(m)	>3	<1	0	0
Aluminium	ppm	ASTM D5185(m)	>20	2	2	1
Plomb	ppm	ASTM D5185(m)	>40	<1	<1	<1
Cuivre	ppm	ASTM D5185(m)	>330	3	<1	1
Étain	ppm	ASTM D5185(m)	>15	0	0	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION











There is no indication of any contamination in the oil.

Silicium	ppm	ASTM D5185(m)	>25	5	3	4
Potassium	ppm	ASTM D5185(m)	>20	2	<1	<1
Essence		WC Method	>5	<1.0	<1.0	<1.0
Glycol		WC Method		NEG	NEG	NEG
% de suie	%	ASTM D7844*	>3	0.1	0.1	0.2
Nitration	Abs/cm	ASTM D7624*	>20	8.4	8.4	7.2
Sulfatation	Abs/.1mm	ASTM D7415*	>30	23.7	25.0	34.8
Eau émulsifiée	scalar	Visual*	>0.2	NEG	NEG	NEG

ÉTAT DU FLUIDE

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		8	2	2
Bore	ppm	ASTM D5185(m)	250	29	2	2
Baryum	ppm	ASTM D5185(m)	10	0	0	0
Molybdène	ppm	ASTM D5185(m)	100	48	52	26
Manganèse	ppm	ASTM D5185(m)		<1	<1	<1
Magnésium	ppm	ASTM D5185(m)	450	643	847	452
Calcium	ppm	ASTM D5185(m)	3000	1632	1504	2343
Phosphore	ppm	ASTM D5185(m)	1150	1054	1046	1170
Zinc	ppm	ASTM D5185(m)	1350	1171	1268	1339
Soufre	ppm	ASTM D5185(m)	4250	2664	2944	3440
Oxydation	Abs/.1mm	ASTM D7414*	>25	21.1	19.8	25.8
Visc 40°C	cSt	ASTM D7279(m)	73	75.0	76.0	67.6
Visc 100°C	cSt	ASTM D7279(m)	10.9	11.2	11.5	11.0
Indice de viscosité (VI)	Scale	ASTM D2270*	138	140	143	154



ISO 17025:2017
Accredited
Laboratory

Laboratoire : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **LES ENTREPRISES MICHAUVILLE INC.**
N° d'échantillon : PC0077605 **Reçu** : 17 Jul 2023
N° de laboratoire : 02570362 **Diagnostic** : 17 Jul 2023
Numéro unique : 5607408 **Diagnostic** : Wes Davis
Analyse : MOB 1 (Additional Tests: KV40, VI)

Pour discuter ce rapport, contacter le service à la clientèle au 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

270 RUE BRUNET
 MONT ST-HILAIRE, QC
 CA J3H 0M6
 Contact: Martin Trudel
 mtrudel@michaudville.com

T:
 F: