



Identité de la machine

1510

Composant

Moteur diesel

Fluide

DIESEL ENGINE OIL SAE 5W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Numéro d'échant.		Client Info		PC0073321	PC0070897	PC0060698
Date d'échant.		Client Info		16 Jul 2023	12 Mar 2023	02 Nov 2022
Âge d la Machine	hrs	Client Info		7618	7101	6678
Âge de l'huile	hrs	Client Info		0	0	0
Âge du filtre	hrs	Client Info		0	0	0
Huile changée		Client Info		N/A	N/A	N/A
Filtre changé		Client Info		N/A	N/A	N/A
Statut de l'échant.				NORMAL	NORMAL	NORMAL

USURE

All component wear rates are normal.

Fer	ppm	ASTM D5185(m)	>100	7	6	7
Chrome	ppm	ASTM D5185(m)	>20	0	0	0
Nickel	ppm	ASTM D5185(m)	>4	0	<1	0
Titane	ppm	ASTM D5185(m)		0	0	<1
Argent	ppm	ASTM D5185(m)	>3	<1	0	0
Aluminium	ppm	ASTM D5185(m)	>20	1	2	2
Plomb	ppm	ASTM D5185(m)	>40	0	0	0
Cuivre	ppm	ASTM D5185(m)	>330	<1	<1	<1
Étain	ppm	ASTM D5185(m)	>15	0	<1	0
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION











There is no indication of any contamination in the oil.

Silicium	ppm	ASTM D5185(m)	>25	8	12	8
Potassium	ppm	ASTM D5185(m)	>20	1	1	2
Essence		WC Method	>5	<1.0	<1.0	<1.0
Glycol		WC Method		NEG	NEG	NEG
% de suie	%	ASTM D7844*	>3	0.1	0	0
Nitration	Abs/cm	ASTM D7624*	>20	7.6	7.7	3.2
Sulfatation	Abs/.1mm	ASTM D7415*	>30	19.5	21.1	9.3
Eau émulsifiée	scalar	Visual*	>0.2	NEG	NEG	NEG

ÉTAT DU FLUIDE

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)	>44	2	1	1
Bore	ppm	ASTM D5185(m)	250	2	1	2
Baryum	ppm	ASTM D5185(m)	10	0	0	0
Molybdène	ppm	ASTM D5185(m)	100	58	60	58
Manganèse	ppm	ASTM D5185(m)		<1	<1	<1
Magnésium	ppm	ASTM D5185(m)	450	970	989	949
Calcium	ppm	ASTM D5185(m)	3000	1095	1168	1207
Phosphore	ppm	ASTM D5185(m)	1150	1052	1099	1073
Zinc	ppm	ASTM D5185(m)	1350	1190	1222	1205
Soufre	ppm	ASTM D5185(m)	4250	2517	2714	2551
Oxydation	Abs/.1mm	ASTM D7414*	>25	15.2	15.2	5.8
Visc 40°C	cSt	ASTM D7279(m)	91	95.4	97.9	94.4
Visc 100°C	cSt	ASTM D7279(m)	14.4	13.9	14.1	13.7
Indice de viscosité (VI)	Scale	ASTM D2270*	164	148	147	146



Laboratoire : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 LES ENTREPRISES MICHAUDVILLE INC.
N° d'échantillon : PC0073321 **Reçu** : 17 Jul 2023
N° de laboratoire : 02570368 **Diagnostiqué** : 17 Jul 2023
Numéro unique : 5607414 **Diagnostiqueur** : Wes Davis
Analyse : MOB 1 (Additional Tests: KV40, VI)

Pour discuter ce rapport, contacter le service à la clientèle au 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

270 RUE BRUNET
 MONT ST-HILAIRE, QC
 CA J3H 0M6
 Contact: Martin Trudel
 mtrudel@michaudville.com
 T:
 F: