



RAPPORT DU LIQUIDE DE REFROIDISSEMENT

CORROSION	NORMAL
CONTAMINANTS	NORMAL
ÉTAT DU LIQUIDE REFROIDISSEMENT	NORMAL

Secteur
MICHAUDVILLE
 Identité de la machine
1201

Composant
Liquide de refroidissement
 Fluide
EXTENDED LIFE COOLANT (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) EXTENDED LIFE COOLANT. Please confirm.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Numéro d'échant.		Client Info		PC0073323	PC0066520	PC0058936
Date d'échant.		Client Info		16 Jul 2023	17 Nov 2022	29 Mar 2022
Âge d la Machine	kms	Client Info		287234	10827	235864
Âge de l'huile	kms	Client Info		0	0	0
Huile changée		Client Info		N/A	N/A	N/A
Statut de l'échant.				NORMAL	NORMAL	NORMAL

CORROSION

All component wear rates are normal.

Fer	ppm	ASTM D5185(m)	>15	3	2	1
Aluminium	ppm	ASTM D5185(m)	>10	<1	3	5
Cuivre	ppm	ASTM D5185(m)	>10	4	2	<1
Plomb	ppm	ASTM D5185(m)	>10	6	0	<1
Étain	ppm	ASTM D5185(m)	>10	2	0	0
Argent	ppm	ASTM D5185(m)	>10	0	0	<1
Zinc	ppm	ASTM D5185(m)	>10	<1	3	3

CONTAMINANTS








There is no indication of any contamination in the coolant.

Calcium	ppm	ASTM D5185(m)	>100	22	21	23
Magnésium	ppm	ASTM D5185(m)	>40	3	3	3
Apparence	scalar	Visual*	NORML	NORML	NORML	NORML
Odeur	scalar	Visual*	NORML	NORML	NORML	NORML
Apparence du liquide de refroidissement		Visual*	Clear	Clear	Clear	Clear

ÉTAT DU LIQUIDE REFROIDISSEMENT

The condition of the coolant is acceptable for the time in service.

Densité		ASTM D1298*		1.082	1.080	1.079
pH	Scale 0-14	ASTM D1287*	9.0	7.70	7.97	7.92
Nitrites	ppm	Alcan Test Kit*		680	520	720
Réserve d'alcalinité	Scale 0-20	ASTM D1121*		4.3	4.5	4.1
Pourcentage de glycol	%	ASTM D3321*	50	62.8	60.4	59.7
Point de congélation	°C	ASTM D3321*	-40	-61	-57	-56
Carboxylate				---	---	---
Silicium	ppm	ASTM D5185(m)		126	84	76
Phosphore	ppm	ASTM D5185(m)		8	65	7
Bore	ppm	ASTM D5185(m)		140	114	126
Molybdène	ppm	ASTM D5185(m)		453	422	487
Sodium	ppm	ASTM D5185(m)		2812	2610	2227
Potassium	ppm	ASTM D5185(m)		1983	2630	2266
Couleur du liquide de refroidissement		Visual*	Orange/R	Red	Orange	Red



ISO 17025:2017
Accredited
Laboratory

Laboratoire : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **LES ENTREPRISES MICHAUDVILLE INC.**
N° d'échantillon : PC0073323 **Reçu** : 17 Jul 2023
N° de laboratoire : 02570501 **Diagnostic** : 17 Jul 2023
Numéro unique : 5607547 **Diagnostic** : Wes Davis
Analyse : COOL

Pour discuter ce rapport, contacter le service à la clientèle au 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

270 RUE BRUNET
 MONT ST-HILAIRE, QC
 CA J3H 0M6
 Contact: Martin Trudel
 mtrudel@michaudville.com

T:
 F: