



RAPPORT D'ANALYSE D'HUILE

USURE	NORMAL
CONTAMINATION	NORMAL
ÉTAT DU FLUIDE	NORMAL

Identité de la machine

51966

Composant

Moteur diesel

Fluide

PETRO CANADA DURON SHP 10W30 (--- LTR)

RECOMMENDATION

Confirm the source of the lubricant being utilized for top-up/fill.
Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Numéro d'échant.		Client Info		WC0836031	---	---
Date d'échant.		Client Info		23 Aug 2023	---	---
Âge d la Machine	mls	Client Info		30620	---	---
Âge de l'huile	mls	Client Info		30620	---	---
Âge du filtre	mls	Client Info		30620	---	---
Huile changée		Client Info		Changed	---	---
Filtre changé		Client Info		Changed	---	---
Statut de l'échant.				NORMAL	---	---

USURE

Metal levels are typical for a components first oil change.

Fer	ppm	ASTM D5185(m)	>100	49	---	---
Chrome	ppm	ASTM D5185(m)	>20	1	---	---
Nickel	ppm	ASTM D5185(m)	>4	<1	---	---
Titane	ppm	ASTM D5185(m)		0	---	---
Argent	ppm	ASTM D5185(m)	>3	<1	---	---
Aluminium	ppm	ASTM D5185(m)	>20	30	---	---
Plomb	ppm	ASTM D5185(m)	>40	4	---	---
Cuivre	ppm	ASTM D5185(m)	>330	16	---	---
Étain	ppm	ASTM D5185(m)	>15	3	---	---
Vanadium	ppm	ASTM D5185(m)		0	---	---

CONTAMINATION











Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Silicium	ppm	ASTM D5185(m)	>25	38	---	---
Potassium	ppm	ASTM D5185(m)	>20	86	---	---
Essence		WC Method	>5	<1.0	---	---
Glycol		WC Method		NEG	---	---
% de suie	%	ASTM D7844*	>3	0.1	---	---
Nitration	Abs/cm	ASTM D7624*	>20	8.3	---	---
Sulfatation	Abs/.1mm	ASTM D7415*	>30	21.3	---	---
Eau émulsifiée	scalar	Visual*	>0.2	NEG	---	---

ÉTAT DU FLUIDE

Additive levels indicate the addition of a different brand, or type of oil.
The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		5	---	---
Bore	ppm	ASTM D5185(m)	2	43	---	---
Baryum	ppm	ASTM D5185(m)	0	5	---	---
Molybdène	ppm	ASTM D5185(m)	50	64	---	---
Manganèse	ppm	ASTM D5185(m)	0	4	---	---
Magnésium	ppm	ASTM D5185(m)	950	465	---	---
Calcium	ppm	ASTM D5185(m)	1050	1739	---	---
Phosphore	ppm	ASTM D5185(m)	995	1020	---	---
Zinc	ppm	ASTM D5185(m)	1180	1180	---	---
Soufre	ppm	ASTM D5185(m)	2600	2455	---	---
Oxydation	Abs/.1mm	ASTM D7414*	>25	17.6	---	---
Visc 100°C	cSt	ASTM D7279(m)	12.00	11.4	---	---



Laboratoire : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
N° d'échantillon : WC0836031 **Reçu** : 15 Sep 2023
N° de laboratoire : 02582657 **Diagnostiqué** : 15 Sep 2023
Numéro unique : 5643722 **Diagnostiqueur** : Wes Davis
Analyse : MOB 1

MANITOU LIN TRANSPORT
 1890 DES SOURCES BOULEVARD
 POINTE CLAIRE, QC
 CA H9R 5B1
 Contact: Eric Marcelin
 emarcelin@manitoulintransport.com
 T: (514)694-5111
 F: (514)694-9739

Pour discuter ce rapport, contacter le service à la clientèle au 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 La validez de los resultados y la interpretación se basan en la muestra y la información proporcionada.