



RAPPORT D'ANALYSE D'HUILE

USURE	NORMAL
CONTAMINATION	NORMAL
ÉTAT DU FLUIDE	NORMAL

Secteur
[205221]
 Identité de la machine
TAPV-ISS-2187
 Composant
Moteur diesel
 Fluide
DIESEL ENGINE OIL SAE 40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DIESEL ENGINE OIL SAE 40. Please confirm.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Numéro d'échant.		Client Info		CU0022111	---	---
Date d'échant.		Client Info		05 Oct 2023	---	---
Âge d la Machine	hrs	Client Info		0	---	---
Âge de l'huile	hrs	Client Info		0	---	---
Âge du filtre	hrs	Client Info		0	---	---
Huile changée		Client Info		N/A	---	---
Filtre changé		Client Info		N/A	---	---
Statut de l'échant.				NORMAL	---	---

USURE

All component wear rates are normal.

Fer	ppm	ASTM D5185(m)	>90	4	---	---
Chrome	ppm	ASTM D5185(m)	>20	0	---	---
Nickel	ppm	ASTM D5185(m)	>2	0	---	---
Titane	ppm	ASTM D5185(m)	>2	0	---	---
Argent	ppm	ASTM D5185(m)	>2	<1	---	---
Aluminium	ppm	ASTM D5185(m)	>20	2	---	---
Plomb	ppm	ASTM D5185(m)	>40	<1	---	---
Cuivre	ppm	ASTM D5185(m)	>330	7	---	---
Étain	ppm	ASTM D5185(m)	>15	0	---	---
Vanadium	ppm	ASTM D5185(m)		0	---	---
Métal blanc	scalar	Visual*	NONE	NONE	---	---
Bronze	scalar	Visual*	NONE	NONE	---	---

CONTAMINATION










There is no indication of any contamination in the oil.

Silicium	ppm	ASTM D5185(m)	>25	8	---	---
Potassium	ppm	ASTM D5185(m)	>20	0	---	---
Essence		WC Method	>3.0	<1.0	---	---
Glycol		WC Method		NEG	---	---
% de suie	%	ASTM D7844*	>6	0	---	---
Nitration	Abs/cm	ASTM D7624*	>20	6.7	---	---
Sulfatation	Abs/.1mm	ASTM D7415*	>30	17.2	---	---
Limon	scalar	Visual*	NONE	NONE	---	---
Débris	scalar	Visual*	NONE	NONE	---	---
Saleté	scalar	Visual*	NONE	NONE	---	---
Apparence	scalar	Visual*	NORML	NORML	---	---
Odeur	scalar	Visual*	NORML	NORML	---	---
Eau émulsifiée	scalar	Visual*	>0.2	NEG	---	---

ÉTAT DU FLUIDE

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)	>216	4	---	---
Bore	ppm	ASTM D5185(m)	250	58	---	---
Baryum	ppm	ASTM D5185(m)	10	1	---	---
Molybdène	ppm	ASTM D5185(m)	100	39	---	---
Manganèse	ppm	ASTM D5185(m)		<1	---	---
Magnésium	ppm	ASTM D5185(m)	450	554	---	---
Calcium	ppm	ASTM D5185(m)	3000	1447	---	---
Phosphore	ppm	ASTM D5185(m)	1150	921	---	---
Zinc	ppm	ASTM D5185(m)	1350	1087	---	---
Soufre	ppm	ASTM D5185(m)	4250	2729	---	---
Oxydation	Abs/.1mm	ASTM D7414*	>25	14.2	---	---
Visc 100°C	cSt	ASTM D7279(m)	14.4	13.3	---	---



ISO 17025:2017
Accredited
Laboratory

Laboratoire : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
N° d'échantillon : CU0022111 **Reçu** : 10 Oct 2023
N° de laboratoire : 02587971 **Diagnostiqué** : 10 Oct 2023
Numéro unique : 5657037 **Diagnostiqueur** : Wes Davis
Analyse : MOB 1 (Additional Tests: Visual)

Pour discuter ce rapport, contacter le service à la clientèle au 1-800-268-2131.

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

La validez de los resultados y la interpretación se basan en la muestra y la información proporcionada.

CUMMINS CANADA ULC
 7200 TRANS CANADA HWY.
 POINTE CLAIRE, QC
 CA H9R 1C2
 Contact: Francois Brault
 Francois.Brault@cummins.com
 T: (514)695-8410
 F: (514)695-5246