



# RAPPORT D'ANALYSE D'HUILE

USURE	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
ÉTAT DU FLUIDE	<b>NORMAL</b>

Secteur

## Equipment de Pont

Identité de la machine

## Obsolete 17C01F#1 Grue Avant Babord (HEPBURN) (S/N C-10079)

Composant

## Grue Avant

Fluide

## PETRO CANADA HYDREX MV ARCTIC 15 (--- GAL)

### RECOMMENDATION

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Numéro d'échant.		Client Info		<b>WC0811223</b>	WC0627035	WC0392714
Date d'échant.		Client Info		<b>23 Oct 2023</b>	30 Mar 2023	13 Mar 2020
Âge d la Machine	hrs	Client Info		<b>347</b>	245	0
Âge de l'huile	hrs	Client Info		<b>347</b>	245	0
Âge du filtre	hrs	Client Info		<b>46</b>	44	0
Huile changée		Client Info		<b>Not Changd</b>	Not Changd	N/A
Filtre changé		Client Info		<b>N/A</b>	Not Changd	N/A
Statut de l'échant.				<b>NORMAL</b>	NORMAL	ABNORMAL

### USURE

All component wear rates are normal.

Fer	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	<1	2
Chrome	ppm	ASTM D5185(m)	>10	<b>0</b>	0	<1
Nickel	ppm	ASTM D5185(m)	>10	<b>&lt;1</b>	0	0
Titane	ppm	ASTM D5185(m)		<b>0</b>	0	0
Argent	ppm	ASTM D5185(m)		<b>&lt;1</b>	0	<1
Aluminium	ppm	ASTM D5185(m)	>10	<b>0</b>	0	<1
Plomb	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	0	2
Cuivre	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	<1	7
Étain	ppm	ASTM D5185(m)	>10	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Métal blanc	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Bronze	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE

### CONTAMINATION










The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Silicium	ppm	ASTM D5185(m)	>15	<b>0</b>	0	0
Potassium	ppm	ASTM D5185(m)	>20	<b>0</b>	0	<1
Particules >4µ		ASTM D7647	>5000	<b>1620</b>	1682	▲ 14096
Particules >6µ		ASTM D7647	>1300	<b>328</b>	446	▲ 1315
Particules >14µ		ASTM D7647	>160	<b>17</b>	34	40
Particules >21µ		ASTM D7647	>40	<b>3</b>	8	16
Particules >38µ		ASTM D7647	>10	<b>0</b>	0	3
Particules >71µ		ASTM D7647	>3	<b>0</b>	0	0
Propreté de l'huile		ISO 4406 (c)	>19/17/14	<b>18/16/11</b>	18/16/12	▲ 21/18/12
Limon	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Débris	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Saleté	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Apparence	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Odeur	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Eau émulsifiée	scalar	Visual*	>0.05	<b>NEG</b>	NEG	NEG

### ÉTAT DU FLUIDE

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1	<1
Bore	ppm	ASTM D5185(m)	0	<b>0</b>	0	<1
Baryum	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	0	<1
Molybdène	ppm	ASTM D5185(m)	0	<b>0</b>	0	<1
Manganèse	ppm	ASTM D5185(m)	0	<b>0</b>	0	0
Magnésium	ppm	ASTM D5185(m)	0	<b>0</b>	0	1
Calcium	ppm	ASTM D5185(m)	50	<b>52</b>	53	93
Phosphore	ppm	ASTM D5185(m)	330	<b>343</b>	379	301
Zinc	ppm	ASTM D5185(m)	430	<b>430</b>	431	383
Soufre	ppm	ASTM D5185(m)	760	<b>2041</b>	2153	1167
Indice d'acidité	mg KOH/g	ASTM D974*	0.70	<b>0.38</b>	0.50	---
Visc 40°C	cSt	ASTM D7279(m)	13.6	<b>15.8</b>	15.9	13.3



**Laboratoire** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**N° d'échantillon** : WC0811223  
**N° de laboratoire** : 02593219  
**Numéro unique** : 5670298  
**Analyse** : MAR 2

**Canadian Coast Guard**  
 CCGS Amundsen, 101 Boul. Champlain  
 Quebec, QC  
 CA G1K 7Y7  
 Contact: Chief Engineer  
 amundsense@ccgs-ngcc.gc.ca  
 T: (418)953-8233  
 F: x:

Pour discuter ce rapport, contacter le service à la clientèle au 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 La validez de los resultados y la interpretación se basan en la muestra y la información proporcionada.