



RAPPORT D'ANALYSE D'HUILE

USURE	NORMAL
CONTAMINATION	NORMAL
ÉTAT DU FLUIDE	NORMAL

Identité de la machine

INTERNATIONAL 3307

Composant

Moteur diesel

Fluid

PETRO CANADA DURON SHP 10W30 (--- LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Numéro d'échant.		Client Info		WC0890005	---	---
Date d'échant.		Client Info		15 Jan 2024	---	---
Âge d la Machine	mls	Client Info		61656	---	---
Âge de l'huile	mls	Client Info		19459	---	---
Âge du filtre	mls	Client Info		19459	---	---
Huile changée		Client Info		Changed	---	---
Filtre changé		Client Info		Changed	---	---
Statut de l'échant.				NORMAL	---	---

USURE

Metal levels are typical for a new component breaking in.

Fer	ppm	ASTM D5185(m)	>100	20	---	---
Chrome	ppm	ASTM D5185(m)	>20	<1	---	---
Nickel	ppm	ASTM D5185(m)	>4	<1	---	---
Titane	ppm	ASTM D5185(m)		0	---	---
Argent	ppm	ASTM D5185(m)	>3	0	---	---
Aluminium	ppm	ASTM D5185(m)	>20	14	---	---
Plomb	ppm	ASTM D5185(m)	>40	0	---	---
Cuivre	ppm	ASTM D5185(m)	>330	1	---	---
Étain	ppm	ASTM D5185(m)	>15	<1	---	---
Vanadium	ppm	ASTM D5185(m)		0	---	---

CONTAMINATION










Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Silicium	ppm	ASTM D5185(m)	>25	4	---	---
Potassium	ppm	ASTM D5185(m)	>20	19	---	---
Essence		WC Method	>2.0	<1.0	---	---
L'eau		WC Method	>0.2	NEG	---	---
Glycol		WC Method		NEG	---	---
% de suie	%	ASTM D7844*	>3	0.3	---	---
Nitration	Abs/cm	ASTM D7624*	>20	8.7	---	---
Sulfatation	Abs/.1mm	ASTM D7415*	>30	20.1	---	---
Eau émulsifiée	scalar	Visual*	>0.2	NEG	---	---

ÉTAT DU FLUIDE

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		1	---	---
Bore	ppm	ASTM D5185(m)	2	1	---	---
Baryum	ppm	ASTM D5185(m)	0	0	---	---
Molybdène	ppm	ASTM D5185(m)	50	59	---	---
Manganèse	ppm	ASTM D5185(m)	0	0	---	---
Magnésium	ppm	ASTM D5185(m)	950	981	---	---
Calcium	ppm	ASTM D5185(m)	1050	1100	---	---
Phosphore	ppm	ASTM D5185(m)	995	1013	---	---
Zinc	ppm	ASTM D5185(m)	1180	1206	---	---
Soufre	ppm	ASTM D5185(m)	2600	2667	---	---
Oxydation	Abs/.1mm	ASTM D7414*	>25	16.7	---	---
Visc 100°C	cSt	ASTM D7279(m)	12.00	11.3	---	---



Laboratoire : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
N° d'échantillon : WC0890005 **Reçu** : 22 Jan 2024
N° de laboratoire : 02610227 **Diagnostiqué** : 23 Jan 2024
Numéro unique : 5711313 **Diagnostiqueur** : Wes Davis
Analyse : MOB 1

MANITOU LIN TRANSPORT
 1890 DES SOURCES BOULEVARD
 POINTE CLAIRE, QC
 CA H9R 5B1
 Contact: Eric Marcelin
 emarcelin@manitoulintransport.com
 T: (514)694-5111
 F: (514)694-9739

Pour discuter ce rapport, contacter le service à la clientèle au 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 La validez de los resultados y la interpretación se basan en la muestra y la información proporcionada.