


Customer: PTRHTF20046	System Information	Sample Information
QUADRA CHEMICALS	System Volume: 20000 ltr	Lab No: 02268423
12925 146TH STREET	Bulk Operating Temp: 482F / 250C	Analyst: Peter Harteveld
EDMONTON, AB T5L 2H6 CANADA	Heating Source:	Sample Date: 02/10/19
Attn: Quadra Samples	Blanket:	Received Date: 02/19/19
Tel:	Fluid: PETRO CANADA PETRO-THERM	Completed: 02/25/19
E-Mail: quadra_samples@quadra.ca	Make:	

Recommendation: The fluid is in good condition and suitable for further use. Please re-sample in 12 months. When filling in the analysis request form please enter fluid service life.


Comments:

Sample Date	Received Date	Fluid Age	Sample Location	Flash Point (COC)	Water (KF)	Viscosity (40°C)	Acid Number	Solids	GCD 10%	GCD 50%	GCD 90%	GCD % < 335°C
	mm/dd/yy			°F/°C	ppm	cSt	mg/KOH/ g	%wt	°F/°C	°F/°C	°F/°C	%
02/10/19	02/19/19	Oy	15-12-50-21WS	424 / 218	12.6	35.7	0.069	0.064	702 / 372	799 / 426	914 / 490	1.35
03/06/18	03/13/18	662y		439 / 226	0.2	35.8	0.01	0.098	706 / 374	798 / 426	892 / 478	0.00
02/23/17	03/03/17	Oy		421 / 216	7.1	35.7	0.100	0.117	704 / 373	805 / 429	915 / 490	0.43
12/09/15	12/14/15	2у		473 / 245	36.8	35.1	0.05	0.049	701 / 372	803 / 429	905 / 485	1.06
07/29/14	08/06/14	5y		448 / 231	401.2	34.9	0.063	0.053	691 / 366	800 / 426	918 / 492	1.75
02/19/14	03/13/14	18y		433 / 223	22.2	35.0	0.053	0.126	707 / 375	813 / 434	924 / 496	1.21
		Baseline	Data	433 / 223		34.2	0.03		720 / 382	817 / 436	900 / 482	1.00






Elemental anaysis results (above) in parts per million (ppm). [10,000 ppm = 1.0%]



% Boiling < 335°C



Historical Comments

03/06/18	The fluid is in excellent condition and suitable for further use. Please re-sample in 12 months and rectify fluid service life at that time.
02/23/17	The fluid is in good condition and suitable for further use. Please re-sample in 12 months.
12/09/15	The fluid is in excellent condition. Please re-sample in 12 months.
07/29/14	The fluid is in good condition. Water content is elevated but not alarming. The difference in water content compared with the sample taken in February 2014 is however large. Please check for source of water. It is recommended to vent off the water vapor via thief hatch. This is most efficient with blanket gas removed but should be done only a few hours at a time to avoid the fluid from oxidizing in contact with outside air at high temperature. Water contamination levels are marginally high. Water contamination levels are marginally high ppm Water contamination levels are marginally high.
02/19/14	The fluid is in good condition and suitable for further use.GCD 90% temperature is slightly elevated indicating some oxidation is taking place. It is recommended to re-sample in 6 months time. (GCD) 90% Distillation Point is marginally high.

Petro-Canada makes no representation or warranty of any kind, either express or implied, as to the accuracy or completeness of the analysis and assumes no responsibility and shall have no liability whatsoever with respect to such analysis, or a party's use of it. Petro-Canada is a division of HollyFrontier Corporation.